

COMPRESSOR DEFINITION

Designation	EG YS90HLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513701192

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4+	[hp]
2 Displacement	7.15	[cm ³] (0.436 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	18.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	10.97	[kg] (24.18 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	7M220MC1/8EA17C1/8M220MC1	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM283NFBYY-53	
6 Start winding resistance	20.94	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	12.03	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	8.20	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	1.40	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	1.60	[A] - Measured according to UL 984
11 Approval boards certification	CCC - OFT	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
770	194	226	135	0.92	4.38	5.70	1.44	1.67

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	405	102	119	89	0.62	2.29	4.51	1.14	1.32
-30 (-22)	572	144	167	106	0.73	3.24	5.35	1.35	1.57
-25 (-13)	758	191	222	125	0.85	4.30	6.10	1.54	1.79
-20 (- 4)	977	246	286	143	0.98	5.56	6.84	1.72	2.00
-15 (+ 5)	1245	314	365	162	1.10	7.10	7.66	1.93	2.24
-10 (+14)	1574	397	461	181	1.22	9.02	8.66	2.18	2.54

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	334	84	98	85	0.60	1.89	3.93	0.99	1.15
-30 (-22)	507	128	149	106	0.73	2.88	4.76	1.20	1.39
-25 (-13)	696	176	204	128	0.87	3.95	5.45	1.37	1.60
-20 (- 4)	915	231	268	151	1.02	5.21	6.08	1.53	1.78
-15 (+ 5)	1178	297	345	174	1.17	6.73	6.74	1.70	1.97
-10 (+14)	1500	378	439	198	1.32	8.59	7.53	1.90	2.21

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	256	64	75	76	0.54	1.45	3.36	0.85	0.98
-30 (-22)	432	109	127	101	0.69	2.45	4.21	1.06	1.23
-25 (-13)	620	156	182	127	0.86	3.52	4.87	1.23	1.43
-20 (- 4)	834	210	244	155	1.04	4.74	5.42	1.36	1.59
-15 (+ 5)	1088	274	319	183	1.23	6.21	5.95	1.50	1.74
-10 (+14)	1397	352	409	213	1.43	8.00	6.55	1.65	1.92

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		