

COMPRESSOR DEFINITION

Designation	VEG Z6H
Nominal Voltage/Frequency	230 V 53-150 Hz
Engineering Number	513802007

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	230 / 53-150	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	BPM		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	187 to 255 V
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	187 to 255 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm ²] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm ²] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	6.36	[cm ³] (0.388 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	430	[ml] (14.54 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	11.31	[kg] (24.93 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	230 V 53-150 Hz 3 ~ (Three phase)	
2 Starting device type	Inverter	
2.1 Starting device	VCC32456XXXX	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	VCC32456XXXXX	
6 Start winding resistance	6.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	6.40	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50/60 Hz)	3.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50/60 Hz)	3.30	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50/60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @230V1600RPM			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
350	88	103	58	0.81	1.99	6.09	1.53	1.78	

TEST CONDITIONS: @230V2000RPM			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
432	109	127	71	0.97	2.45	6.10	1.54	1.79	

TEST CONDITIONS: @230V3000RPM			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
685	173	201	113	1.46	3.89	6.08	1.53	1.78	

TEST CONDITIONS: @230V4500RPM			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
928	234	272	163	2.06	5.27	5.70	1.44	1.67	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @230V1600RPM		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
°C (°F)										
-35 (-31)	214	54	63	36	0.47	1.21	5.88	1.48	1.72	
-30 (-22)	294	74	86	44	0.58	1.67	6.68	1.68	1.96	
-25 (-13)	382	96	112	51	0.68	2.17	7.54	1.90	2.21	
-20 (- 4)	483	122	142	57	0.76	2.75	8.52	2.15	2.50	
-15 (+ 5)	602	152	176	62	0.83	3.44	9.70	2.45	2.84	
-10 (+14)	744	188	218	67	0.90	4.26	11.15	2.81	3.27	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @230V1600RPM		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	189	48	55	36	0.48	1.07	5.26	1.32	1.54
-30	(-22)	267	67	78	44	0.58	1.51	6.01	1.51	1.76
-25	(-13)	353	89	104	52	0.69	2.01	6.73	1.69	1.97
-20	(- 4)	454	114	133	60	0.80	2.58	7.48	1.88	2.19
-15	(+ 5)	573	145	168	68	0.91	3.27	8.33	2.10	2.44
-10	(+14)	718	181	210	76	1.02	4.11	9.36	2.36	2.74

TEST CONDITIONS: @230V1600RPM		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	154	39	45	37	0.52	0.87	4.18	1.05	1.23
-30	(-22)	228	57	67	45	0.61	1.29	5.04	1.27	1.48
-25	(-13)	311	78	91	54	0.71	1.77	5.76	1.45	1.69
-20	(- 4)	410	103	120	64	0.83	2.33	6.43	1.62	1.88
-15	(+ 5)	529	133	155	74	0.97	3.02	7.11	1.79	2.08
-10	(+14)	674	170	197	85	1.13	3.86	7.86	1.98	2.30

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		