

COMPRESSOR DEFINITION

Designation	EG US70HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513701197

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5+	[hp]
2 Displacement	5.56	[cm ³] (0.339 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	10.33	[kg] (22.77 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA14C1/8EA21C1/QPS2-A4R7MG1/QPS2-A4R7MG1 090	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM427LFBYY-53	
6 Start winding resistance	9.14	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.17	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	13.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.30	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	2.70	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
684	172	200	126	1.57	3.89	5.41	1.36	1.59

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	335	85	98	81	1.01	1.90	4.16	1.05	1.22
-30 (-22)	497	125	146	99	1.23	2.82	4.98	1.26	1.46
-25 (-13)	700	176	205	119	1.48	3.97	5.85	1.47	1.72
-20 (- 4)	938	236	275	139	1.73	5.34	6.77	1.71	1.98
-15 (+ 5)	1207	304	354	157	1.97	6.89	7.73	1.95	2.26
-10 (+14)	1501	378	440	173	2.19	8.60	8.72	2.20	2.56

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	286	72	84	71	0.92	1.62	4.02	1.01	1.18
-30 (-22)	426	107	125	92	1.17	2.42	4.63	1.17	1.36
-25 (-13)	616	155	180	116	1.46	3.50	5.28	1.33	1.55
-20 (- 4)	848	214	249	141	1.77	4.83	5.98	1.51	1.75
-15 (+ 5)	1119	282	328	166	2.09	6.39	6.72	1.69	1.97
-10 (+14)	1422	358	417	190	2.40	8.15	7.50	1.89	2.20

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	224	56	66	64	0.83	1.27	3.49	0.88	1.02
-30 (-22)	340	86	100	86	1.09	1.93	4.01	1.01	1.18
-25 (-13)	512	129	150	112	1.41	2.91	4.58	1.15	1.34
-20 (- 4)	735	185	215	141	1.77	4.18	5.19	1.31	1.52
-15 (+ 5)	1004	253	294	171	2.16	5.73	5.85	1.47	1.71
-10 (+14)	1313	331	385	200	2.55	7.52	6.54	1.65	1.92

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		