

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EM T56CLP |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 513306089 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR-RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 255 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 255 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 6.9 | [kgf/cm ²] (98 psig) | / °C - °F |
| 9.2 Peak | 7.8 | [kgf/cm ²] (111 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | 1/6 | [hp] |
| 2 Displacement | 9.04 | [cm ³] (0.552 cu.in) |
| 2.1 Bore [mm] | 24.000 | |
| 2.2 Stroke [mm] | 20.000 | |
| 3 Lubricant charge | 180 | [ml] (6.09 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 7.65 | [kg] (16.87 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | V230 | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 2.5(280) | [µF(VAC minimum)] |
| 5 Motor protection | T0357/07 | |
| 6 Start winding resistance | 24.75 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 21.55 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | 5.50 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | 0.64 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | CE - UKCA - VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|--------------------------------|----------------------------------|--|---------------------------|--|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 529 | 133 | 155 | 115 | 0.63 | 1.66 | 4.62 | 1.16 | 1.35 |

E - PERFORMANCE - CURVES

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 291 | 73 | 85 | 75 | 0.54 | 0.91 | 3.84 | 0.97 | 1.13 |
| -30 (-22) | 386 | 97 | 113 | 91 | 0.58 | 1.21 | 4.27 | 1.08 | 1.25 |
| -25 (-13) | 510 | 129 | 150 | 107 | 0.61 | 1.60 | 4.78 | 1.20 | 1.40 |
| -20 (- 4) | 664 | 167 | 194 | 124 | 0.64 | 2.09 | 5.37 | 1.35 | 1.57 |
| -15 (+ 5) | 847 | 213 | 248 | 140 | 0.68 | 2.67 | 6.03 | 1.52 | 1.77 |
| -10 (+14) | 1061 | 267 | 311 | 156 | 0.72 | 3.35 | 6.77 | 1.71 | 1.98 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 262 | 66 | 77 | 77 | 0.55 | 0.82 | 3.41 | 0.86 | 1.00 |
| -30 (-22) | 362 | 91 | 106 | 93 | 0.59 | 1.13 | 3.91 | 0.98 | 1.14 |
| -25 (-13) | 487 | 123 | 143 | 110 | 0.62 | 1.53 | 4.43 | 1.12 | 1.30 |
| -20 (- 4) | 639 | 161 | 187 | 128 | 0.66 | 2.01 | 4.98 | 1.25 | 1.46 |
| -15 (+ 5) | 817 | 206 | 240 | 147 | 0.70 | 2.57 | 5.55 | 1.40 | 1.63 |
| -10 (+14) | 1023 | 258 | 300 | 167 | 0.75 | 3.23 | 6.14 | 1.55 | 1.80 |

| | | | | | | | | | |
|-------------------------------|----------------------------|----------|--------------------|--------------------------------|--|----------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | | ASHRAE32 Static | | (Condensing temperature 65°C (+149°F)) | | | | |
| Evaporating temperature | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 (-31) | 233 | 59 | 68 | 76 | 0.54 | 0.73 | 3.07 | 0.77 | 0.90 |
| -30 (-22) | 336 | 85 | 98 | 93 | 0.58 | 1.05 | 3.58 | 0.90 | 1.05 |
| -25 (-13) | 461 | 116 | 135 | 113 | 0.63 | 1.45 | 4.07 | 1.03 | 1.19 |
| -20 (- 4) | 609 | 153 | 178 | 134 | 0.67 | 1.91 | 4.53 | 1.14 | 1.33 |
| -15 (+ 5) | 781 | 197 | 229 | 158 | 0.72 | 2.46 | 4.96 | 1.25 | 1.45 |
| -10 (+14) | 977 | 246 | 286 | 183 | 0.78 | 3.08 | 5.34 | 1.35 | 1.57 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|--------------------------------|------|--------------------------|
| 1 Base plate | European Standard EUEM | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 8.1 +0.10/+0.00 | [mm] | (0.319" +0.004"/+0.000") |
| 3.1.1 Material | Copper(OD) | | |
| 3.1.2 Shape | Slanted 42° up + 45° to Back | | |
| 3.2 DISCHARGE | 5.1 +0.10/+0.00 | [mm] | (0.201" +0.004"/+0.000") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted parallel BP+24°to Back | | |
| 3.3 PROCESS | 6 +0.08/-0.08 | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material | Copper(OD) | | |
| 3.3.2 Shape | Slanted 43° up + 45° to Back | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |