

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EG AS80HLR |
| Nominal Voltage/Frequency | 115-127 V 60 Hz |
| Engineering Number | 513701043 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|------------------------------------|-----------------------------------|-------------------------|-------------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-134a | | |
| 3 Nominal voltage and frequency | 115-127 / 60 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR-CSIR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static/Fan | - | 98 to 140 V |
| 8.2 LBP (43°C Ambient temperature) | Static/Fan | - | 98 to 140 V |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing temperature | | | |
| 9.1 Operating | 14.2 | [kgf/cm²] (202 psig) | / °C - °F |
| 9.2 Peak | 15.9 | [kgf/cm²] (226 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|---------------|--|
| 1 Commercial designation | 1/4+ | [hp] |
| 2 Displacement | 6.36 | [cm ³] (0.388 cu.in) |
| 2.1 Bore [mm] | 22.500 | |
| 2.2 Stroke [mm] | 16.000 | |
| 3 Lubricant charge | 230 | [ml] (7.78 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ESTER / ISO10 | |
| 4 Weight (with oil charge) | 9.84 | [kg] (21.69 lb.) |
| 5 Nitrogen charge | 0.2 to 0.3 | [kgf/cm ²] (2.84 to 4.27 psig) |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 115-127 V 60 Hz 1 ~ (Single phase) | |
| 2 Starting device type | Current Relay | |
| 2.1 Starting device | 213516001/213516585 | |
| 3 Start capacitor | 233-280(140) | [µF(VAC minimum)] |
| 4 Run capacitor | - | [µF(VAC minimum)] |
| 5 Motor protection | 4TM762NFBZZ-53 | |
| 6 Start winding resistance | 6.55 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 3.05 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (60 Hz) | 29.00 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (60 Hz) | 5.94 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (60 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | CE - TUV - UKCA - UL - VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|--------------------------------|----------|-----|------------------------------------|--------------------------------------|--|-------------------------------|---|-------|
| TEST CONDITIONS: @115V60Hz | | | ASHRAELBP32 Static | | Evaporating temperature (Condensing temperature | | -23.3°C (-9.94°F) 54.4°C (129.92°F)) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 812 | 205 | 238 | 155 | 2.03 | 4.61 | 5.24 | 1.32 | 1.54 |

E - PERFORMANCE - CURVES

| TEST CONDITIONS: @115V60Hz | | ASHRAE32 Static | | | (Condensing temperature 45°C (+113°F)) | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|---|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 401 | 101 | 117 | 102 | 1.33 | 2.27 | 3.93 | 0.99 | 1.15 |
| -30 | (-22) | 602 | 152 | 176 | 125 | 1.62 | 3.41 | 4.80 | 1.21 | 1.41 |
| -25 | (-13) | 823 | 207 | 241 | 147 | 1.91 | 4.67 | 5.60 | 1.41 | 1.64 |
| -20 | (- 4) | 1074 | 271 | 315 | 169 | 2.19 | 6.11 | 6.38 | 1.61 | 1.87 |
| -15 | (+ 5) | 1366 | 344 | 400 | 190 | 2.46 | 7.80 | 7.20 | 1.81 | 2.11 |
| -10 | (+14) | 1710 | 431 | 501 | 210 | 2.73 | 9.80 | 8.13 | 2.05 | 2.38 |

| TEST CONDITIONS: @115V60Hz | | ASHRAE32 Static | | | (Condensing temperature 55°C (+131°F)) | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|---|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 324 | 82 | 95 | 91 | 1.20 | 1.83 | 3.55 | 0.90 | 1.04 |
| -30 | (-22) | 517 | 130 | 151 | 118 | 1.55 | 2.93 | 4.34 | 1.09 | 1.27 |
| -25 | (-13) | 734 | 185 | 215 | 145 | 1.91 | 4.17 | 5.04 | 1.27 | 1.48 |
| -20 | (- 4) | 988 | 249 | 289 | 173 | 2.27 | 5.62 | 5.69 | 1.44 | 1.67 |
| -15 | (+ 5) | 1287 | 324 | 377 | 202 | 2.64 | 7.35 | 6.37 | 1.61 | 1.87 |
| -10 | (+14) | 1644 | 414 | 482 | 230 | 3.01 | 9.42 | 7.13 | 1.80 | 2.09 |

| TEST CONDITIONS: @115V60Hz | | ASHRAE32 Static | | | (Condensing temperature 65°C (+149°F)) | | | | | |
|-------------------------------|-------|--------------------|----------|-----|---|---------------------|---------------|-----------------|-----------|-------|
| Evaporating temperature | | Cooling capacity | | | Power consumption | Current consumption | Gas flow rate | EFFICIENCY RATE | | |
| | | +/- 5% | | | +/- 5% | +/- 5% | +/- 5% | +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 248 | 63 | 73 | 83 | 1.11 | 1.41 | 2.99 | 0.75 | 0.88 |
| -30 | (-22) | 426 | 107 | 125 | 112 | 1.48 | 2.41 | 3.78 | 0.95 | 1.11 |
| -25 | (-13) | 633 | 159 | 185 | 143 | 1.87 | 3.59 | 4.44 | 1.12 | 1.30 |
| -20 | (- 4) | 881 | 222 | 258 | 175 | 2.28 | 5.01 | 5.05 | 1.27 | 1.48 |
| -15 | (+ 5) | 1181 | 298 | 346 | 209 | 2.71 | 6.74 | 5.65 | 1.42 | 1.66 |
| -10 | (+14) | 1542 | 389 | 452 | 243 | 3.15 | 8.84 | 6.31 | 1.59 | 1.85 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|---------------------------------------|------|--------------------------|
| 1 Base plate | European Standard EG/F/AMEM Version 2 | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Straight | | |
| 3.2 DISCHARGE | 4.94 +0.08/-0.08 | [mm] | (0.194" +0.003"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Straight | | |
| 3.3 PROCESS | 6.5 +0.12/-0.08 | [mm] | (0.256" +0.005"/-0.003") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Straight | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |