

COMPRESSOR DEFINITION

Designation	EM T32CLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513306014

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.96	[cm ³] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	7.3	[kg] (16.09 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0224/07	
6 Start winding resistance	32.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	31.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	3.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.59	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
359	90	105	76	0.59	1.13	4.73	1.19	1.39

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	182	46	53	54	0.56	0.57	3.39	0.85	0.99
-30 (-22)	275	69	81	63	0.56	0.86	4.32	1.09	1.27
-25 (-13)	375	94	110	71	0.58	1.18	5.29	1.33	1.55
-20 (- 4)	484	122	142	77	0.61	1.52	6.31	1.59	1.85
-15 (+ 5)	604	152	177	82	0.63	1.90	7.37	1.86	2.16
-10 (+14)	738	186	216	87	0.64	2.33	8.47	2.13	2.48

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	170	43	50	56	0.55	0.53	3.04	0.77	0.89
-30 (-22)	256	65	75	66	0.55	0.80	3.89	0.98	1.14
-25 (-13)	352	89	103	74	0.57	1.10	4.76	1.20	1.39
-20 (- 4)	458	116	134	81	0.61	1.44	5.64	1.42	1.65
-15 (+ 5)	579	146	170	88	0.64	1.82	6.55	1.65	1.92
-10 (+14)	716	180	210	96	0.67	2.26	7.46	1.88	2.19

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))			
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	155	39	45	57	0.55	0.48	2.72	0.69	0.80
-30 (-22)	233	59	68	66	0.55	0.73	3.51	0.89	1.03
-25 (-13)	323	81	95	75	0.58	1.01	4.30	1.08	1.26
-20 (- 4)	427	108	125	84	0.62	1.34	5.07	1.28	1.49
-15 (+ 5)	547	138	160	93	0.66	1.72	5.84	1.47	1.71
-10 (+14)	685	173	201	104	0.69	2.16	6.60	1.66	1.93

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	137	35	40	57	0.57	0.43	2.38	0.60	0.70
-30	(-22)	207	52	61	66	0.57	0.65	3.13	0.79	0.92
-25	(-13)	290	73	85	76	0.59	0.91	3.85	0.97	1.13
-20	(- 4)	390	98	114	86	0.63	1.23	4.54	1.14	1.33
-15	(+ 5)	508	128	149	98	0.67	1.60	5.19	1.31	1.52
-10	(+14)	647	163	190	111	0.71	2.04	5.80	1.46	1.70

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel BP+24°to Back		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 45° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		