

COMPRESSOR DEFINITION

Designation	EG YS70HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513701071

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	5.56	[cm ³] (0.339 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	230	[ml] (7.78 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	10.3	[kg] (22.71 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA14C1/8EA21C1/QPS2-A4R7MG1/QPS2-A4R7MG1 090	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM427LFBYY-53	
6 Start winding resistance	6.97	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	3.69	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	13.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	2.35	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	2.75	[A] - Measured according to UL 984
11 Approval boards certification	CE - NOM - TUV - UKCA - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
700	176	205	127	1.54	3.98	5.53	1.39	1.62

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	335	85	98	79	0.99	1.90	4.24	1.07	1.24
-30 (-22)	497	125	146	97	1.21	2.82	5.07	1.28	1.49
-25 (-13)	700	176	205	117	1.45	3.97	5.96	1.50	1.75
-20 (- 4)	938	236	275	136	1.70	5.34	6.89	1.74	2.02
-15 (+ 5)	1207	304	354	155	1.93	6.89	7.86	1.98	2.30
-10 (+14)	1501	378	440	170	2.15	8.60	8.88	2.24	2.60

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	286	72	84	70	0.90	1.62	4.09	1.03	1.20
-30 (-22)	426	107	125	91	1.15	2.42	4.71	1.19	1.38
-25 (-13)	616	155	180	114	1.43	3.50	5.38	1.35	1.58
-20 (- 4)	848	214	249	139	1.73	4.83	6.09	1.53	1.78
-15 (+ 5)	1119	282	328	163	2.04	6.39	6.84	1.72	2.01
-10 (+14)	1422	358	417	187	2.35	8.15	7.64	1.92	2.24

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	224	56	66	63	0.81	1.27	3.55	0.90	1.04
-30 (-22)	340	86	100	85	1.07	1.93	4.08	1.03	1.20
-25 (-13)	512	129	150	110	1.39	2.91	4.66	1.17	1.37
-20 (- 4)	735	185	215	138	1.74	4.18	5.29	1.33	1.55
-15 (+ 5)	1004	253	294	168	2.11	5.73	5.95	1.50	1.74
-10 (+14)	1313	331	385	197	2.49	7.52	6.66	1.68	1.95

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		