

### COMPRESSOR DEFINITION

Designation	EM X32CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513309502

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm <sup>2</sup> ] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm <sup>2</sup> ] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.96	[cm <sup>3</sup> ] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.88	[kg] (17.37 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD-220V0.6	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	2(380)/2.5(380)	[µF(VAC minimum)]
5 Motor protection	4TM 110NFBYY-73	
6 Start winding resistance	34.75	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	37.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.60	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.40	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - IRAM - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			<b>CECOMAFLBP</b> Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
250	63	73	54	0.25	0.95	4.60	1.16	1.35

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	163	41	48	38	0.18	0.57	4.26	1.07	1.25
-30 (-22)	221	56	65	45	0.21	0.77	4.94	1.24	1.45
-25 (-13)	291	73	85	52	0.24	1.01	5.64	1.42	1.65
-20 (- 4)	376	95	110	59	0.27	1.31	6.42	1.62	1.88
-15 (+ 5)	479	121	140	65	0.30	1.67	7.32	1.84	2.14
-10 (+14)	606	153	177	72	0.33	2.12	8.37	2.11	2.45

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	125	32	37	37	0.18	0.48	3.39	0.86	0.99
-30 (-22)	184	46	54	45	0.21	0.70	4.03	1.01	1.18
-25 (-13)	249	63	73	54	0.25	0.95	4.62	1.16	1.35
-20 (- 4)	326	82	96	62	0.28	1.25	5.21	1.31	1.53
-15 (+ 5)	417	105	122	71	0.32	1.60	5.85	1.47	1.71
-10 (+14)	527	133	155	80	0.36	2.02	6.58	1.66	1.93

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	94	24	28	36	0.17	0.40	2.60	0.65	0.76
-30 (-22)	152	38	44	46	0.21	0.64	3.26	0.82	0.95
-25 (-13)	213	54	62	56	0.25	0.90	3.81	0.96	1.12
-20 (- 4)	281	71	82	66	0.30	1.19	4.29	1.08	1.26
-15 (+ 5)	360	91	105	76	0.35	1.53	4.75	1.20	1.39
-10 (+14)	453	114	133	87	0.40	1.93	5.23	1.32	1.53

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 90° up + 24° to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		