

COMPRESSOR DEFINITION

Designation	EM X20CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	898AA88

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	3.97	[cm ³] (0.242 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.8	[kg] (17.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	MI.E-START 2021	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	2(440)	[μF(VAC minimum)]
5 Motor protection	AE23AHNX	
6 Start winding resistance	34.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	47.80	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.18	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	IRAM - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
157	40	46	37	0.17	0.60	4.23	1.07	1.24

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	105	27	31	27	0.13	0.37	3.82	0.96	1.12
-30	(-22)	145	36	42	32	0.14	0.50	4.58	1.16	1.34
-25	(-13)	194	49	57	36	0.16	0.68	5.40	1.36	1.58
-20	(- 4)	253	64	74	40	0.18	0.88	6.29	1.58	1.84
-15	(+ 5)	323	81	95	45	0.20	1.13	7.25	1.83	2.12
-10	(+14)	403	102	118	49	0.22	1.41	8.29	2.09	2.43

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	81	20	24	28	0.13	0.31	2.92	0.74	0.86
-30	(-22)	115	29	34	32	0.15	0.44	3.57	0.90	1.05
-25	(-13)	158	40	46	37	0.17	0.60	4.25	1.07	1.24
-20	(- 4)	210	53	62	42	0.19	0.80	4.95	1.25	1.45
-15	(+ 5)	272	69	80	48	0.22	1.04	5.69	1.43	1.67
-10	(+14)	344	87	101	53	0.25	1.32	6.48	1.63	1.90

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	61	15	18	27	0.13	0.26	2.24	0.56	0.66
-30	(-22)	91	23	27	32	0.15	0.38	2.82	0.71	0.83
-25	(-13)	128	32	38	38	0.17	0.54	3.39	0.86	0.99
-20	(- 4)	174	44	51	44	0.20	0.74	3.96	1.00	1.16
-15	(+ 5)	228	58	67	51	0.23	0.97	4.52	1.14	1.33
-10	(+14)	292	74	86	57	0.26	1.25	5.10	1.28	1.49

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42°		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		