

COMPRESSOR DEFINITION

Designation	EM Y26CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	894HA73

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low-Medium Back Pressure		
4.1 Evaporating temperature range	-35°C to -5°C	(-31°F to 23°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm ²] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm ²] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.19	[cm ³] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	7.7	[kg] (16.98 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MSDA3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	2.5(450)	[µF(VAC minimum)]
5 Motor protection	4TM110NFBYY-153	
6 Start winding resistance	28.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	43.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.25	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.70	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFB Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
218	55	64	54	0.24	0.83	4.02	1.01	1.18	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	134	34	39	40	0.19	0.47	3.39	0.85	0.99
-30	(-22)	189	48	55	46	0.21	0.66	4.14	1.04	1.21
-25	(-13)	253	64	74	52	0.24	0.88	4.85	1.22	1.42
-20	(- 4)	328	83	96	59	0.27	1.14	5.56	1.40	1.63
-15	(+ 5)	415	105	122	66	0.29	1.45	6.30	1.59	1.85
-10	(+14)	517	130	151	73	0.32	1.81	7.10	1.79	2.08
-5	(+23)	635	160	186	79	0.35	2.23	7.99	2.01	2.34

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	111	28	33	41	0.19	0.42	2.75	0.69	0.81
-30	(-22)	161	40	47	47	0.21	0.61	3.43	0.86	1.01
-25	(-13)	217	55	64	54	0.24	0.83	4.03	1.02	1.18
-20	(- 4)	283	71	83	62	0.27	1.08	4.59	1.16	1.35
-15	(+ 5)	360	91	106	70	0.31	1.38	5.14	1.30	1.51
-10	(+14)	450	113	132	79	0.34	1.73	5.71	1.44	1.67
-5	(+23)	555	140	163	88	0.38	2.14	6.34	1.60	1.86

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 65°C (+149°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	84	21	25	40	0.19	0.36	2.09	0.53	0.61
-30	(-22)	129	33	38	47	0.21	0.54	2.75	0.69	0.81
-25	(-13)	180	45	53	55	0.24	0.76	3.29	0.83	0.96
-20	(- 4)	238	60	70	64	0.28	1.01	3.75	0.95	1.10
-15	(+ 5)	306	77	90	74	0.32	1.30	4.16	1.05	1.22
-10	(+14)	386	97	113	85	0.37	1.64	4.55	1.15	1.33
-5	(+23)	479	121	140	96	0.42	2.05	4.96	1.25	1.45

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.95 +0.05/+0.05	[mm]	(0.195" +0.002"/+0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		