

COMPRESSOR DEFINITION

Designation	EM Y26CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	9999

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR-RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.19	[cm ³] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.35	[kg] (16.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	2.5(440)	[μF(VAC minimum)]
5 Motor protection	T0882/07	
6 Start winding resistance	27.30	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	38.00	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.70	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.25	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
212	53	62	51	0.25	0.81	4.17	1.05	1.22

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	167	42	49	36	0.20	0.53	4.59	1.16	1.35
-30	(-22)	226	57	66	42	0.22	0.73	5.43	1.37	1.59
-25	(-13)	295	74	87	47	0.23	0.95	6.31	1.59	1.85
-20	(- 4)	379	95	111	52	0.25	1.22	7.26	1.83	2.13
-15	(+ 5)	479	121	140	57	0.27	1.54	8.34	2.10	2.44
-10	(+14)	599	151	175	62	0.28	1.93	9.59	2.42	2.81

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	135	34	40	36	0.20	0.47	3.71	0.93	1.09
-30	(-22)	191	48	56	43	0.22	0.67	4.44	1.12	1.30
-25	(-13)	256	64	75	50	0.24	0.89	5.15	1.30	1.51
-20	(- 4)	331	83	97	56	0.26	1.16	5.88	1.48	1.72
-15	(+ 5)	421	106	123	63	0.29	1.47	6.67	1.68	1.95
-10	(+14)	528	133	155	70	0.31	1.85	7.56	1.90	2.21

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	98	25	29	35	0.20	0.37	2.82	0.71	0.83
-30	(-22)	152	38	44	43	0.22	0.58	3.54	0.89	1.04
-25	(-13)	212	53	62	51	0.25	0.81	4.18	1.05	1.22
-20	(- 4)	280	71	82	59	0.27	1.07	4.77	1.20	1.40
-15	(+ 5)	360	91	105	67	0.30	1.38	5.36	1.35	1.57
-10	(+14)	454	115	133	76	0.34	1.75	5.99	1.51	1.75

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	59	15	17	33	0.19	0.25	1.79	0.45	0.52
-30	(-22)	111	28	33	42	0.22	0.47	2.59	0.65	0.76
-25	(-13)	167	42	49	51	0.25	0.70	3.24	0.82	0.95
-20	(- 4)	229	58	67	61	0.28	0.97	3.78	0.95	1.11
-15	(+ 5)	300	76	88	71	0.31	1.28	4.26	1.07	1.25
-10	(+14)	383	97	112	81	0.35	1.64	4.72	1.19	1.38

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel to Base Plate		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		