

COMPRESSOR DEFINITION

Designation	EM Z26CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	898HA89

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.19	[cm ³] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.88	[kg] (17.37 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	2.5(440)	[μF(VAC minimum)]
5 Motor protection	T0285/07	
6 Start winding resistance	28.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	42.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.20	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
212	53	62	49	0.23	0.81	4.31	1.09	1.26

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	116	29	34	35	0.17	0.40	3.28	0.83	0.96
-30	(-22)	183	46	54	41	0.20	0.64	4.39	1.11	1.29
-25	(-13)	249	63	73	47	0.22	0.87	5.27	1.33	1.55
-20	(- 4)	322	81	94	53	0.25	1.12	6.07	1.53	1.78
-15	(+ 5)	408	103	120	59	0.27	1.42	6.92	1.74	2.03
-10	(+14)	515	130	151	64	0.29	1.80	7.96	2.01	2.33

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	85	21	25	34	0.16	0.32	2.49	0.63	0.73
-30	(-22)	150	38	44	42	0.20	0.57	3.53	0.89	1.03
-25	(-13)	212	53	62	49	0.23	0.81	4.29	1.08	1.26
-20	(- 4)	278	70	82	57	0.26	1.06	4.91	1.24	1.44
-15	(+ 5)	356	90	104	64	0.29	1.36	5.52	1.39	1.62
-10	(+14)	451	114	132	72	0.32	1.73	6.26	1.58	1.83

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	55	14	16	32	0.15	0.23	1.70	0.43	0.50
-30	(-22)	115	29	34	41	0.19	0.48	2.73	0.69	0.80
-25	(-13)	171	43	50	50	0.23	0.72	3.42	0.86	1.00
-20	(- 4)	228	58	67	59	0.27	0.97	3.91	0.99	1.15
-15	(+ 5)	295	74	86	68	0.31	1.25	4.34	1.09	1.27
-10	(+14)	377	95	110	77	0.35	1.61	4.84	1.22	1.42

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 42°		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		