

### COMPRESSOR DEFINITION

Designation	EM T26CLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513306090

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR-RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.19	[cm <sup>3</sup> ] (0.317 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.07	[kg] (15.59 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	2.5(280)	[µF(VAC minimum)]
5 Motor protection	AE24AHN10	
6 Start winding resistance	26.20	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	45.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.80	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.32	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			<b>CECOMAFLBP</b> Static		Evaporating temperature (Condensing temperature	-25°C (-13°F) 55°C (131°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
212	53	62	60	0.33	0.81	3.52	0.89	1.03

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	116	29	34	46	0.30	0.40	2.51	0.63	0.74
-30 (-22)	183	46	54	53	0.31	0.64	3.46	0.87	1.01
-25 (-13)	249	63	73	59	0.32	0.87	4.25	1.07	1.24
-20 (- 4)	322	81	94	65	0.34	1.12	4.97	1.25	1.46
-15 (+ 5)	408	103	120	72	0.35	1.42	5.70	1.44	1.67
-10 (+14)	515	130	151	78	0.36	1.80	6.53	1.65	1.91

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	85	21	25	46	0.30	0.32	1.86	0.47	0.55
-30 (-22)	150	38	44	53	0.32	0.57	2.79	0.70	0.82
-25 (-13)	212	53	62	60	0.33	0.81	3.52	0.89	1.03
-20 (- 4)	278	70	82	67	0.35	1.06	4.13	1.04	1.21
-15 (+ 5)	356	90	104	76	0.36	1.36	4.70	1.18	1.38
-10 (+14)	451	114	132	84	0.38	1.73	5.32	1.34	1.56

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	55	14	16	45	0.30	0.23	1.23	0.31	0.36
-30 (-22)	115	29	34	53	0.32	0.48	2.13	0.54	0.62
-25 (-13)	171	43	50	61	0.34	0.72	2.79	0.70	0.82
-20 (- 4)	228	58	67	70	0.36	0.97	3.27	0.82	0.96
-15 (+ 5)	295	74	86	81	0.37	1.25	3.67	0.93	1.08
-10 (+14)	377	95	110	92	0.39	1.61	4.08	1.03	1.19

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42° up + 45° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 90° up + 24° to Back		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 43° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		