

### COMPRESSOR DEFINITION

Designation	EM Y46CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	897FA83

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR-RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.96	[cm <sup>3</sup> ] (0.486 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	17.600	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.7	[kg] (16.98 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	4(440)	[μF(VAC minimum)]
5 Motor protection	T0881/07	
6 Start winding resistance	17.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	22.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.39	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			<b>CECOMAFLBP</b> Static		Evaporating temperature (Condensing temperature	<b>-25°C (-13°F)</b> <b>55°C (131°F)</b>		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
348	88	102	80	0.40	1.33	4.37	1.10	1.28

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature <b>45°C (+113°F)</b> )				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
<b>-35 (-31)</b>	213	54	62	57	0.36	0.74	3.76	0.95	1.10
<b>-30 (-22)</b>	300	76	88	66	0.37	1.04	4.51	1.14	1.32
<b>-25 (-13)</b>	403	102	118	77	0.38	1.40	5.24	1.32	1.53
<b>-20 (- 4)</b>	526	132	154	88	0.41	1.83	5.97	1.51	1.75
<b>-15 (+ 5)</b>	670	169	196	100	0.43	2.34	6.75	1.70	1.98
<b>-10 (+14)</b>	837	211	245	111	0.46	2.93	7.59	1.91	2.23

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature <b>55°C (+131°F)</b> )				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
<b>-35 (-31)</b>	181	46	53	56	0.37	0.69	3.25	0.82	0.95
<b>-30 (-22)</b>	258	65	76	67	0.37	0.98	3.82	0.96	1.12
<b>-25 (-13)</b>	349	88	102	80	0.40	1.33	4.36	1.10	1.28
<b>-20 (- 4)</b>	457	115	134	94	0.43	1.75	4.89	1.23	1.43
<b>-15 (+ 5)</b>	584	147	171	108	0.46	2.24	5.44	1.37	1.60
<b>-10 (+14)</b>	732	184	214	121	0.49	2.81	6.05	1.53	1.77

TEST CONDITIONS: @220V50Hz			<b>CECOMAF</b> Static		(Condensing temperature <b>65°C (+149°F)</b> )				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
<b>-35 (-31)</b>	145	37	43	55	0.36	0.61	2.62	0.66	0.77
<b>-30 (-22)</b>	215	54	63	69	0.37	0.91	3.11	0.78	0.91
<b>-25 (-13)</b>	298	75	87	83	0.40	1.26	3.56	0.90	1.04
<b>-20 (- 4)</b>	394	99	115	99	0.44	1.67	3.99	1.00	1.17
<b>-15 (+ 5)</b>	506	128	148	115	0.48	2.15	4.42	1.11	1.30
<b>-10 (+14)</b>	637	161	187	130	0.51	2.72	4.90	1.23	1.44

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.95 +0.05/+0.05	[mm]	(0.195" +0.002"/+0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		