

COMPRESSOR DEFINITION

Designation	EM Y40CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	897DA96

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR-RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.23	[cm ³] (0.441 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.65	[kg] (16.87 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	MI2021	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(440)	[µF(VAC minimum)]
5 Motor protection	AE37FN10	
6 Start winding resistance	25.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	24.60	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	3.90	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.38	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
310	78	91	72	0.38	1.18	4.29	1.08	1.26

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	196	49	57	49	0.32	0.68	4.00	1.01	1.17
-30	(-22)	272	68	80	59	0.34	0.95	4.60	1.16	1.35
-25	(-13)	361	91	106	69	0.37	1.26	5.23	1.32	1.53
-20	(- 4)	466	118	137	79	0.40	1.63	5.90	1.49	1.73
-15	(+ 5)	591	149	173	89	0.43	2.06	6.63	1.67	1.94
-10	(+14)	738	186	216	99	0.46	2.58	7.44	1.87	2.18

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	159	40	47	49	0.32	0.60	3.23	0.81	0.95
-30	(-22)	229	58	67	61	0.35	0.87	3.76	0.95	1.10
-25	(-13)	310	78	91	72	0.38	1.18	4.28	1.08	1.26
-20	(- 4)	405	102	119	84	0.41	1.55	4.83	1.22	1.41
-15	(+ 5)	518	131	152	96	0.45	1.98	5.41	1.36	1.58
-10	(+14)	651	164	191	108	0.49	2.50	6.03	1.52	1.77

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	130	33	38	49	0.32	0.55	2.64	0.66	0.77
-30	(-22)	191	48	56	62	0.35	0.81	3.09	0.78	0.90
-25	(-13)	262	66	77	75	0.39	1.11	3.51	0.88	1.03
-20	(- 4)	345	87	101	88	0.43	1.46	3.92	0.99	1.15
-15	(+ 5)	444	112	130	102	0.48	1.89	4.35	1.10	1.27
-10	(+14)	560	141	164	117	0.52	2.39	4.80	1.21	1.41

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		