

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | EM 2C55CLT |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 513304505 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | Operating voltage range | | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 255 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 255 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 7.7 | [kgf/cm ²] (109 psig) | / °C - °F |
| 9.2 Peak (gauge) | 9.8 | [kgf/cm ²] (139 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 9.04 | [cm ³] (0.552 cu.in) |
| 2.1 Bore [mm] | 24.000 | |
| 2.2 Stroke [mm] | 20.000 | |
| 3 Lubricant charge | 150 | [ml] (5.07 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | MINERAL / ISO5 | |
| 4 Weight (with oil charge) | 8.36 | [kg] (18.43 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | TSD | |
| 2.1 Starting device | TSD-220V | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 5(310)/4(300) | [µF(VAC minimum)] |
| 5 Motor protection | 4TM189NFBYY-53 | |
| 6 Start winding resistance | 18.00 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 20.80 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | 4.30 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | 0.65 | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] - Measured according to UL 984 |
| 11 Approval boards certification | VDE | |

D - PERFORMANCE - CHECK POINT DATA

E - PERFORMANCE - CURVES

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|--------------------------------|------|--------------------------|
| 1 Base plate | European Standard EUEM | | |
| 2 Tray holder | Yes | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° up + 45° to Back | | |
| 3.2 DISCHARGE | 4.94 +0.08/-0.08 | [mm] | (0.194" +0.003"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted parallel BP+24°to Back | | |
| 3.3 PROCESS | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Slanted 45° up + 45° to Back | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |