

### COMPRESSOR DEFINITION

|                           |                 |
|---------------------------|-----------------|
| Designation               | EM 2C66CLT      |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number        | 513304506       |

### A - APPLICATION / LIMIT WORKING CONDITIONS

|  |                                   |                                   |           |
|--|-----------------------------------|-----------------------------------|-----------|
| 1 Type                                     | Hermetic reciprocating compressor |                                   |           |
| 2 Refrigerant                              | R-600a                            |                                   |           |
| 3 Nominal voltage and frequency            | 220-240 / 50                      | [ V / Hz ]                        |           |
| 4 Application type                         | Low Back Pressure                 |                                   |           |
| 4.1 Evaporating temperature range          | -35°C to -10°C                    | (-31°F to 14°F)                   |           |
| 5 Motor type                               | RSCR                              |                                   |           |
| 6 Starting torque                          | LST - Low Starting Torque         |                                   |           |
| 7 Expansion device                         | Capillary tube                    |                                   |           |
| 8 Compressor cooling                       | Operating voltage range           |                                   |           |
|  |                                   | 50 Hz                             | 60 Hz     |
| 8.1 LBP (32°C Ambient temperature)         | Static                            | 198 to 255 V                      | -         |
| 8.2 LBP (43°C Ambient temperature)         | Static                            | 198 to 255 V                      | -         |
| 8.3 HBP (32°C Ambient temperature)         | -                                 | -                                 | -         |
| 8.4 HBP (43°C Ambient temperature)         | -                                 | -                                 | -         |
| 9 Maximum condensing pressures/temperature |                                   |                                   |           |
| 9.1 Operating (gauge)                      | 7.7                               | [kgf/cm <sup>2</sup> ] (109 psig) | / °C - °F |
| 9.2 Peak (gauge)                           | 9.8                               | [kgf/cm <sup>2</sup> ] (139 psig) | / °C - °F |
| 10 Maximum winding temperature             | 130                               | [ °C ]                            |           |

### B - MECHANICAL DATA

|                               |                |                                  |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation      | 1/5            | [hp]                             |
| 2 Displacement                | 10.61          | [cm <sup>3</sup> ] (0.647 cu.in) |
| 2.1 Bore [mm]                 | 26.000         |                                  |
| 2.2 Stroke [mm]               | 20.000         |                                  |
| 3 Lubricant charge            | 150            | [ml] (5.07 fl.oz.)               |
| 3.1 Lubricants approved       |                |                                  |
| 3.2 Lubricants type/viscosity | MINERAL / ISO5 |                                  |
| 4 Weight (with oil charge)    | 8.36           | [kg] (18.43 lb.)                 |
| 5 Nitrogen charge             | -              | [kgf/cm <sup>2</sup> ]           |

### C - ELETRICAL DATA

|  |                                    |                                    |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) |                                    |
| 2 Starting device type                       | PTC                                |                                    |
| 2.1 Starting device                          | V230                               |                                    |
| 3 Start capacitor                            | -                                  | [µF(VAC minimum)]                  |
| 4 Run capacitor                              | 5(310)/4(310)                      | [µF(VAC minimum)]                  |
| 5 Motor protection                           | T0225/07                           |                                    |
| 6 Start winding resistance                   | 13.10                              | [Ω at 25°C (77°F)] +/- 8%          |
| 7 Run winding resistance                     | 18.50                              | [Ω at 25°C (77°F)] +/- 8%          |
| 8 LRA - Locked rotor amperage (50 Hz)        | 5.10                               | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz)     | 0.77                               | [A] - Measured according to UL 984 |
| 10 FLA - Full Load Amperage HBP (50 Hz)      | -                                  | [A] - Measured according to UL 984 |
| 11 Approval boards certification             | VDE                                |                                    |

**D - PERFORMANCE - CHECK POINT DATA**

---

**E - PERFORMANCE - CURVES**

---

### F - EXTERNAL CHARACTERISTICS

|                         |                                |      |                          |
|-------------------------|--------------------------------|------|--------------------------|
| 1 Base plate            | European Standard EUEM         |      |                          |
| 2 Tray holder           | Yes                            |      |                          |
| 3 Connectors            |                                |      |                          |
| 3.1 SUCTION             | 6.1 +0.10/+0.00                | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material          | Copper                         |      |                          |
| 3.1.2 Shape             | Slanted 42° up + 45° to Back   |      |                          |
| 3.2 DISCHARGE           | 4.9 +0.10/-0.05                | [mm] | (0.193" +0.004"/-0.002") |
| 3.2.1 Material          | Copper                         |      |                          |
| 3.2.2 Shape             | Slanted parallel BP+24°to Back |      |                          |
| 3.3 PROCESS             | 6.1 +0.10/+0.00                | [mm] | (0.240" +0.004"/+0.000") |
| 3.3.1 Material          | Copper                         |      |                          |
| 3.3.2 Shape             | Slanted 45° up + 45° to Back   |      |                          |
| 3.4 Oil cooler (Copper) | No                             | [mm] |                          |
| 3.5 Connector sealing   | Rubber Plugs                   |      |                          |