

COMPRESSOR DEFINITION

| | |
|---------------------------|-----------------|
| Designation | NB T1114Y |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number | 810CA47 |

A - APPLICATION / LIMIT WORKING CONDITIONS

| | | | |
|--------------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type | Hermetic reciprocating compressor | | |
| 2 Refrigerant | R-600a | | |
| 3 Nominal voltage and frequency | 220-240 / 50 | [V / Hz] | |
| 4 Application type | Low Back Pressure | | |
| 4.1 Evaporating temperature range | -35°C to -10°C | (-31°F to 14°F) | |
| 5 Motor type | RSIR-RSCR | | |
| 6 Starting torque | LST - Low Starting Torque | | |
| 7 Expansion device | Capillary tube | | |
| 8 Compressor cooling | | Operating voltage range | |
| | | 50 Hz | 60 Hz |
| 8.1 LBP (32°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.2 LBP (43°C Ambient temperature) | Static | 198 to 254 V | - |
| 8.3 HBP (32°C Ambient temperature) | - | - | - |
| 8.4 HBP (43°C Ambient temperature) | - | - | - |
| 9 Maximum condensing pressures/temperature | | | |
| 9.1 Operating (gauge) | 7.7 | [kgf/cm ²] (109 psig) | / °C - °F |
| 9.2 Peak (gauge) | 9.8 | [kgf/cm ²] (139 psig) | / °C - °F |
| 10 Maximum winding temperature | 130 | [°C] | |

B - MECHANICAL DATA

| | | |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation | | [hp] |
| 2 Displacement | 9.99 | [cm ³] (0.610 cu.in) |
| 2.1 Bore [mm] | 26.497 | |
| 2.2 Stroke [mm] | 18.120 | |
| 3 Lubricant charge | 350 | [ml] (11.84 fl.oz.) |
| 3.1 Lubricants approved | | |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 | |
| 4 Weight (with oil charge) | 10.17 | [kg] (22.42 lb.) |
| 5 Nitrogen charge | - | [kgf/cm ²] |

C - ELETRICAL DATA

| | | |
|----------------------------------------------|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) | |
| 2 Starting device type | PTC | |
| 2.1 Starting device | 2019 | |
| 3 Start capacitor | - | [µF(VAC minimum)] |
| 4 Run capacitor | 4(450) | [µF(VAC minimum)] |
| 5 Motor protection | AD23FQ10 | |
| 6 Start winding resistance | 23.40 | [Ω at 25°C (77°F)] +/- 8% |
| 7 Run winding resistance | 15.40 | [Ω at 25°C (77°F)] +/- 8% |
| 8 LRA - Locked rotor amperage (50 Hz) | 5.10 | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz) | 0.46 | [A] |
| 10 FLA - Full Load Amperage HBP (50 Hz) | - | [A] |
| 11 Approval boards certification | VDE | |

D - PERFORMANCE - CHECK POINT DATA

| | | | | | | | | |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|----------------------------------------------------|---------------------------|-------------------------------|-------|
| TEST CONDITIONS: @220V50Hz | | | CECOMAFLBP Static | | Evaporating temperature (Condensing temperature | | -25°C (-13°F) 55°C (131°F) | |
| Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| 410 | 103 | 120 | 102 | 0.42 | 1.56 | 4.03 | 1.02 | 1.18 |

E - PERFORMANCE - CURVES

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|-----------------------------|----------------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | CECOMAF Static | | | | (Condensing temperature 45°C (+113°F)) | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 271 | 68 | 80 | 73 | 0.60 | 0.94 | 3.71 | 0.94 | 1.09 |
| -30 | (-22) | 363 | 92 | 106 | 85 | 0.63 | 1.26 | 4.31 | 1.09 | 1.26 |
| -25 | (-13) | 484 | 122 | 142 | 98 | 0.68 | 1.68 | 4.95 | 1.25 | 1.45 |
| -20 | (- 4) | 632 | 159 | 185 | 112 | 0.73 | 2.20 | 5.63 | 1.42 | 1.65 |
| -15 | (+ 5) | 805 | 203 | 236 | 127 | 0.78 | 2.81 | 6.33 | 1.59 | 1.85 |
| -10 | (+14) | 1003 | 253 | 294 | 143 | 0.84 | 3.51 | 7.04 | 1.77 | 2.06 |

| | | | | | | | | | | |
|-------------------------------|-------|----------------------------|----------|-----|-----------------------------|----------------------------------------|-------------------------|---------------------------|-----------|-------|
| TEST CONDITIONS: @220V50Hz | | CECOMAF Static | | | | (Condensing temperature 55°C (+131°F)) | | | | |
| Evaporating temperature | | Cooling capacity +/- 5% | | | Power consumption +/- 5% | Current consumption +/- 5% | Gas flow rate +/- 5% | EFFICIENCY RATE +/- 7% | | |
| °C | (°F) | [Btu/h] | [kcal/h] | [W] | [W] | [A] | [kg/h] | [Btu/Wh] | [kcal/Wh] | [W/W] |
| -35 | (-31) | 213 | 54 | 62 | 77 | 0.61 | 0.81 | 2.77 | 0.70 | 0.81 |
| -30 | (-22) | 300 | 76 | 88 | 89 | 0.65 | 1.14 | 3.38 | 0.85 | 0.99 |
| -25 | (-13) | 411 | 104 | 120 | 102 | 0.69 | 1.57 | 4.02 | 1.01 | 1.18 |
| -20 | (- 4) | 545 | 137 | 160 | 117 | 0.75 | 2.08 | 4.65 | 1.17 | 1.36 |
| -15 | (+ 5) | 701 | 177 | 205 | 133 | 0.82 | 2.68 | 5.28 | 1.33 | 1.55 |
| -10 | (+14) | 876 | 221 | 257 | 149 | 0.88 | 3.36 | 5.90 | 1.49 | 1.73 |

F - EXTERNAL CHARACTERISTICS

| | | | |
|-------------------------|--------------------------------|------|--------------------------|
| 1 Base plate | European Standard | | |
| 2 Tray holder | No | | |
| 3 Connectors | | | |
| 3.1 SUCTION | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material | Copper | | |
| 3.1.2 Shape | Slanted 42° | | |
| 3.2 DISCHARGE | 4.94 +0.08/-0.08 | [mm] | (0.194" +0.003"/-0.003") |
| 3.2.1 Material | Copper | | |
| 3.2.2 Shape | Slanted parallel to Base Plate | | |
| 3.3 PROCESS | 6.1 +0.10/+0.00 | [mm] | (0.240" +0.004"/+0.000") |
| 3.3.1 Material | Copper | | |
| 3.3.2 Shape | Slanted 42° | | |
| 3.4 Oil cooler (Copper) | No | [mm] | |
| 3.5 Connector sealing | Rubber Plugs | | |