

COMPRESSOR DEFINITION

Designation	NB Y1118Y
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	816BA42

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	7.7	[kgf/cm ²] (109 psig)	/ °C - °F
9.2 Peak (gauge)	9.8	[kgf/cm ²] (139 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	10.6	[kg] (23.37 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(450)	[µF(VAC minimum)]
5 Motor protection	AD18BQ10	
6 Start winding resistance	23.20	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	15.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
625	158	183	133	0.63	2.38	4.70	1.18	1.38

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	462	116	135	90	0.44	1.48	5.15	1.30	1.51
-30	(-22)	591	149	173	102	0.49	1.90	5.84	1.47	1.71
-25	(-13)	772	195	226	115	0.55	2.48	6.75	1.70	1.98
-20	(- 4)	1007	254	295	128	0.61	3.23	7.84	1.98	2.30
-15	(+ 5)	1295	326	380	143	0.67	4.17	9.06	2.28	2.65
-10	(+14)	1640	413	481	158	0.74	5.29	10.35	2.61	3.03

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	426	107	125	98	0.46	1.48	4.36	1.10	1.28
-30	(-22)	543	137	159	111	0.52	1.89	4.90	1.23	1.44
-25	(-13)	702	177	206	125	0.59	2.45	5.61	1.41	1.64
-20	(- 4)	907	229	266	140	0.66	3.16	6.45	1.63	1.89
-15	(+ 5)	1158	292	339	157	0.73	4.05	7.37	1.86	2.16
-10	(+14)	1457	367	427	175	0.82	5.10	8.32	2.10	2.44

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	361	91	106	100	0.48	1.38	3.63	0.91	1.06
-30	(-22)	472	119	138	115	0.55	1.80	4.08	1.03	1.19
-25	(-13)	617	156	181	132	0.62	2.35	4.66	1.17	1.36
-20	(- 4)	800	202	234	150	0.70	3.05	5.32	1.34	1.56
-15	(+ 5)	1021	257	299	170	0.79	3.91	6.01	1.51	1.76
-10	(+14)	1281	323	375	192	0.89	4.92	6.69	1.69	1.96

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel to Base Plate		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		