

COMPRESSOR DEFINITION

Designation	NB U1118Y.
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	815DA45

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	14.28	[cm ³] (0.871 cu.in)
2.1 Bore [mm]	30.157	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	MINERAL / ISO7	
4 Weight (with oil charge)	10.75	[kg] (23.70 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(450)	[µF(VAC minimum)]
5 Motor protection	T0062/07	
6 Start winding resistance	22.90	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	15.68	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
603	152	177	135	0.63	2.30	4.47	1.13	1.31

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	495	125	145	92	0.46	1.59	5.39	1.36	1.58
-30	(-22)	610	154	179	105	0.51	1.96	5.89	1.48	1.73
-25	(-13)	772	194	226	118	0.56	2.48	6.59	1.66	1.93
-20	(- 4)	987	249	289	132	0.62	3.17	7.47	1.88	2.19
-15	(+ 5)	1260	318	369	147	0.69	4.05	8.51	2.14	2.49
-10	(+14)	1598	403	468	164	0.76	5.15	9.70	2.44	2.84

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	439	111	129	97	0.47	1.52	4.52	1.14	1.32
-30	(-22)	546	138	160	111	0.53	1.90	4.93	1.24	1.44
-25	(-13)	691	174	202	127	0.60	2.41	5.48	1.38	1.60
-20	(- 4)	879	222	258	143	0.66	3.07	6.15	1.55	1.80
-15	(+ 5)	1116	281	327	161	0.74	3.90	6.94	1.75	2.03
-10	(+14)	1408	355	413	180	0.83	4.93	7.82	1.97	2.29

TEST CONDITIONS: @220V50Hz		CECOMAF Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	367	92	107	100	0.48	1.39	3.67	0.92	1.08
-30	(-22)	472	119	138	116	0.55	1.80	4.04	1.02	1.18
-25	(-13)	606	153	177	134	0.63	2.31	4.50	1.13	1.32
-20	(- 4)	773	195	227	153	0.71	2.96	5.04	1.27	1.48
-15	(+ 5)	980	247	287	174	0.80	3.76	5.63	1.42	1.65
-10	(+14)	1232	311	361	197	0.90	4.73	6.26	1.58	1.84

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	280	71	82	100	0.48	1.19	2.84	0.71	0.83
-30	(-22)	390	98	114	119	0.56	1.64	3.23	0.81	0.95
-25	(-13)	519	131	152	140	0.65	2.19	3.67	0.92	1.07
-20	(- 4)	672	169	197	163	0.75	2.84	4.12	1.04	1.21
-15	(+ 5)	855	215	250	188	0.86	3.63	4.58	1.15	1.34
-10	(+14)	1073	270	314	215	0.98	4.58	5.03	1.27	1.47

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal
2 Tray holder	No
3 Connectors	
3.1 SUCTION	6.45 +0.10/+0.00 [mm] (0.254" +0.004"/+0.000")
3.1.1 Material	Copper
3.1.2 Shape	Slanted 42°
3.2 DISCHARGE	4.94 +0.08/-0.08 [mm] (0.194" +0.003"/-0.003")
3.2.1 Material	Copper
3.2.2 Shape	Slanted parallel to Base Plate
3.3 PROCESS	6.45 +0.10/+0.00 [mm] (0.254" +0.004"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Slanted 42°
3.4 Oil cooler (Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs