

COMPRESSOR DEFINITION

Designation	EM T40CLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	895DA77

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.23	[cm ³] (0.441 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	16.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.35	[kg] (16.20 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	AE64FS	
6 Start winding resistance	26.70	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	27.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.53	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
310	78	91	90	0.67	1.18	3.44	0.87	1.01

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	239	60	70	65	0.62	0.76	3.68	0.93	1.08
-30	(-22)	323	81	95	74	0.63	1.04	4.37	1.10	1.28
-25	(-13)	423	107	124	82	0.65	1.36	5.15	1.30	1.51
-20	(- 4)	542	136	159	90	0.67	1.74	6.01	1.51	1.76
-15	(+ 5)	681	172	200	98	0.70	2.19	6.93	1.75	2.03
-10	(+14)	845	213	248	107	0.72	2.72	7.90	1.99	2.31

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	208	53	61	67	0.62	0.72	3.10	0.78	0.91
-30	(-22)	282	71	83	77	0.64	0.98	3.64	0.92	1.07
-25	(-13)	370	93	109	87	0.66	1.29	4.26	1.07	1.25
-20	(- 4)	476	120	139	96	0.69	1.66	4.94	1.24	1.45
-15	(+ 5)	601	151	176	106	0.72	2.10	5.67	1.43	1.66
-10	(+14)	748	188	219	116	0.75	2.62	6.43	1.62	1.88

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	169	43	50	68	0.62	0.64	2.52	0.64	0.74
-30	(-22)	234	59	68	79	0.64	0.89	2.96	0.75	0.87
-25	(-13)	311	78	91	90	0.67	1.18	3.46	0.87	1.01
-20	(- 4)	404	102	118	101	0.70	1.54	4.01	1.01	1.17
-15	(+ 5)	514	130	151	112	0.74	1.97	4.59	1.16	1.35
-10	(+14)	645	163	189	124	0.78	2.48	5.20	1.31	1.52

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	131	33	38	68	0.62	0.55	1.92	0.48	0.56
-30	(-22)	187	47	55	81	0.64	0.79	2.30	0.58	0.67
-25	(-13)	254	64	74	93	0.67	1.07	2.73	0.69	0.80
-20	(- 4)	335	84	98	105	0.71	1.42	3.20	0.81	0.94
-15	(+ 5)	432	109	126	118	0.75	1.84	3.69	0.93	1.08
-10	(+14)	548	138	160	131	0.81	2.34	4.18	1.05	1.22

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		