

COMPRESSOR DEFINITION

Designation	F F7,5HBKW
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	513200631

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Low-Medium-High Back Pressure		
4.1 Evaporating temperature range	-35°C to 15°C	(-31°F to 59°F)	
5 Motor type	RSIR/CSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	103 to 135 V
8.2 LBP (43°C Ambient temperature)	Static	-	103 to 135 V
8.3 HBP (32°C Ambient temperature)	Fan	-	103 to 135 V
8.4 HBP (43°C Ambient temperature)	Fan	-	103 to 135 V
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5+	[hp]
2 Displacement	6.92	[cm ³] (0.422 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.79	[kg] (23.79 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	213516060/213516124	
3 Start capacitor	189-227(110)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	MRT30AIK-5590	
6 Start winding resistance	10.35	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.65	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	25.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	3.30	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	3.90	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP32 Fan		Evaporating temperature (Condensing temperature)		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2940	741	861	384	3.99		7.66	1.93	2.24

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature)		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
695	175	204	178	2.44	3.95	3.90	0.98	1.14

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature)		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
695	175	204	178	2.44	3.95	3.90	0.98	1.14

E - PERFORMANCE - CURVES

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper plated steel		
3.1.2 Shape	Slanted		
3.2 DISCHARGE	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.2.1 Material	Copper plated steel		
3.2.2 Shape	Slanted		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper plated steel		
3.3.2 Shape	Slanted		
3.4 Oil cooler (Copper)	6.5 +0.09/-0.09	[mm]	(0.256" +0.004"/-0.004")
3.5 Connector sealing	Rubber Plugs		