

COMPRESSOR DEFINITION

Designation	NT 6222GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	922CA04

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	17.39	[cm ³] (1.061 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17.2	[kg] (37.92 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA3N3C-122	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	15(440)	[µF(VAC minimum)]
5 Motor protection	T0624/G9	
6 Start winding resistance	9.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	2.30	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ - IRAM	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
9174	2312	2688	1114	5.54	75.53	8.24	2.08	2.41

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	4038	1018	1183	686	3.75	25.62	5.88	1.48	1.72
-15	(+ 5)	5051	1273	1480	719	3.86	32.26	7.04	1.77	2.06
-10	(+14)	6239	1572	1828	760	4.01	40.08	8.22	2.07	2.41
-5	(+23)	7617	1920	2232	808	4.20	49.28	9.43	2.38	2.76
0	(+32)	9203	2319	2697	861	4.42	60.06	10.68	2.69	3.13
+5	(+41)	11012	2775	3227	918	4.65	72.63	11.99	3.02	3.51
+10	(+50)	13062	3292	3828	976	4.89	87.18	13.38	3.37	3.92

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3393	855	994	716	3.86	23.77	4.74	1.19	1.39
-15	(+ 5)	4282	1079	1255	764	4.06	30.18	5.60	1.41	1.64
-10	(+14)	5316	1340	1558	819	4.29	37.72	6.49	1.64	1.90
-5	(+23)	6514	1641	1909	879	4.54	46.60	7.41	1.87	2.17
0	(+32)	7890	1988	2312	942	4.81	57.01	8.38	2.11	2.46
+5	(+41)	9462	2384	2773	1006	5.08	69.16	9.41	2.37	2.76
+10	(+50)	11246	2834	3295	1070	5.34	83.25	10.51	2.65	3.08

TEST CONDITIONS: @220V50Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2761	696	809	765	4.05	21.74	3.61	0.91	1.06
-15	(+ 5)	3504	883	1027	822	4.31	27.73	4.26	1.07	1.25
-10	(+14)	4366	1100	1279	884	4.58	34.80	4.94	1.24	1.45
-5	(+23)	5362	1351	1571	950	4.87	43.16	5.64	1.42	1.65
0	(+32)	6508	1640	1907	1017	5.15	53.01	6.40	1.61	1.88
+5	(+41)	7822	1971	2292	1083	5.43	64.55	7.22	1.82	2.12
+10	(+50)	9320	2349	2731	1147	5.69	77.98	8.12	2.05	2.38

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		