

COMPRESSOR DEFINITION

Designation	NT 2160U
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	842AD04

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-290		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	Low Back Pressuure R290		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expantion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	19.1	[kgf/cm ²] (272 psig)	/ °C - °F
9.2 Peak (gauge)	21.2	[kgf/cm ²] (301 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	17.39	[cm ³] (1.061 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	16.8	[kg] (37.04 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH0051-08	
3 Start capacitor	64-77(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0659/J5	
6 Start winding resistance	6.49	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.69	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	28.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @208V60Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)		
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]	
2825	712	828	618	4.12	8.41	4.57	1.15	1.34	

E - PERFORMANCE - CURVES

TEST CONDITIONS: @208V60Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1453	366	426	381	3.27	4.29	3.81	0.96	1.12
-35	(-31)	1865	470	547	430	3.44	5.52	4.34	1.09	1.27
-30	(-22)	2395	603	702	482	3.62	7.10	4.97	1.25	1.46
-25	(-13)	3042	767	891	537	3.82	9.05	5.66	1.43	1.66
-20	(- 4)	3808	960	1116	595	4.04	11.36	6.41	1.61	1.88
-15	(+ 5)	4693	1183	1375	655	4.28	14.06	7.17	1.81	2.10
-10	(+14)	5696	1435	1669	717	4.54	17.14	7.94	2.00	2.33

TEST CONDITIONS: @208V60Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1327	334	389	393	3.31	3.92	3.38	0.85	0.99
-35	(-31)	1703	429	499	444	3.48	5.04	3.84	0.97	1.13
-30	(-22)	2195	553	643	501	3.68	6.51	4.38	1.10	1.28
-25	(-13)	2803	706	821	564	3.92	8.34	4.96	1.25	1.45
-20	(- 4)	3528	889	1034	632	4.19	10.53	5.58	1.40	1.63
-15	(+ 5)	4370	1101	1281	706	4.49	13.09	6.19	1.56	1.81
-10	(+14)	5329	1343	1562	785	4.84	16.03	6.79	1.71	1.99

TEST CONDITIONS: @208V60Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1207	304	354	408	3.34	3.56	2.95	0.74	0.87
-35	(-31)	1554	392	455	460	3.52	4.60	3.38	0.85	0.99
-30	(-22)	2014	508	590	522	3.74	5.97	3.86	0.97	1.13
-25	(-13)	2590	653	759	592	4.01	7.70	4.37	1.10	1.28
-20	(- 4)	3280	827	961	671	4.34	9.78	4.89	1.23	1.43
-15	(+ 5)	4086	1030	1197	758	4.71	12.24	5.40	1.36	1.58
-10	(+14)	5007	1262	1467	854	5.14	15.06	5.86	1.48	1.72

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		