

### COMPRESSOR DEFINITION

Designation	EG ZS100HLC
Nominal Voltage/Frequency	220-240 V 50-60 Hz
Engineering Number	513701063

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50-60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	198 to 255 V
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	198 to 255 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	16.2	[kgf/cm <sup>2</sup> ] (230 psig)	/ °C - °F
9.2 Peak (gauge)	20.6	[kgf/cm <sup>2</sup> ] (293 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/3	[hp]
2 Displacement	7.95	[cm <sup>3</sup> ] (0.485 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	20.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO7	
4 Weight (with oil charge)	11.28	[kg] (24.87 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50-60 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD-220V0.6	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(380)/5(400)	[µF(VAC minimum)]
5 Motor protection	BT104-105	
6 Start winding resistance	25.08	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	9.84	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50/60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50/60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50/60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
855	215	251	145	0.82	4.86	5.90	1.49	1.73

TEST CONDITIONS: @220V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1050	265	308	173	0.83	5.97	6.08	1.53	1.78

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	442	111	129	95	0.55	2.50	4.65	1.17	1.36
-30	(-22)	620	156	182	112	0.64	3.52	5.57	1.40	1.63
-25	(-13)	828	209	242	129	0.73	4.70	6.43	1.62	1.88
-20	(- 4)	1074	271	315	148	0.82	6.11	7.28	1.83	2.13
-15	(+ 5)	1369	345	401	167	0.93	7.82	8.17	2.06	2.39
-10	(+14)	1724	434	505	188	1.04	9.88	9.14	2.30	2.68

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	362	91	106	91	0.53	2.05	3.99	1.00	1.17
-30	(-22)	554	140	162	112	0.64	3.14	4.92	1.24	1.44
-25	(-13)	769	194	225	134	0.75	4.36	5.75	1.45	1.69
-20	(- 4)	1016	256	298	156	0.87	5.78	6.52	1.64	1.91
-15	(+ 5)	1306	329	383	179	0.99	7.45	7.28	1.84	2.13
-10	(+14)	1648	415	483	204	1.13	9.44	8.07	2.03	2.37

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	263	66	77	77	0.46	1.49	3.43	0.87	1.01	
-30 (-22)	471	119	138	105	0.61	2.67	4.39	1.11	1.29	
-25 (-13)	695	175	204	133	0.76	3.94	5.18	1.31	1.52	
-20 (- 4)	945	238	277	161	0.91	5.38	5.87	1.48	1.72	
-15 (+ 5)	1231	310	361	190	1.07	7.03	6.50	1.64	1.90	
-10 (+14)	1564	394	458	220	1.23	8.96	7.11	1.79	2.08	

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static			(Condensing temperature 45°C (+113°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	543	137	159	114	0.55	3.07	4.77	1.20	1.40	
-30 (-22)	762	192	223	134	0.64	4.32	5.72	1.44	1.68	
-25 (-13)	1017	256	298	155	0.74	5.77	6.60	1.66	1.93	
-20 (- 4)	1319	332	387	177	0.83	7.51	7.47	1.88	2.19	
-15 (+ 5)	1682	424	493	200	0.94	9.60	8.38	2.11	2.46	
-10 (+14)	2117	534	620	225	1.05	12.13	9.38	2.36	2.75	

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static			(Condensing temperature 55°C (+131°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	445	112	130	109	0.53	2.52	4.09	1.03	1.20	
-30 (-22)	681	172	200	134	0.64	3.86	5.05	1.27	1.48	
-25 (-13)	945	238	277	160	0.76	5.36	5.90	1.49	1.73	
-20 (- 4)	1248	314	366	187	0.88	7.10	6.69	1.69	1.96	
-15 (+ 5)	1604	404	470	215	1.01	9.15	7.47	1.88	2.19	
-10 (+14)	2024	510	593	244	1.14	11.60	8.28	2.09	2.43	

TEST CONDITIONS: @220V60Hz		ASHRAE32 Static			(Condensing temperature 65°C (+149°F))					
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%			
	°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	323	81	95	92	0.46	1.83	3.52	0.89	1.03	
-30 (-22)	578	146	170	126	0.61	3.28	4.50	1.13	1.32	
-25 (-13)	854	215	250	159	0.76	4.85	5.32	1.34	1.56	
-20 (- 4)	1160	292	340	193	0.91	6.60	6.02	1.52	1.76	
-15 (+ 5)	1512	381	443	228	1.07	8.63	6.66	1.68	1.95	
-10 (+14)	1921	484	563	264	1.24	11.00	7.29	1.84	2.14	

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		