

### COMPRESSOR DEFINITION

Designation	EG YS80CLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513701270

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	11.14	[cm <sup>3</sup> ] (0.680 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	21.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	10.97	[kg] (24.18 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17C1/8EA17E63/QPS2-A22MG1/QPS2-A22MG1 092/QPS2	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	4TM283KFBYY-53	
6 Start winding resistance	23.32	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	12.33	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50/60 Hz)	8.10/7.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50/60 Hz)	1.37/1.22	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50/60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - IRAM - UKCA - VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			<b>CECOMAFLBP</b> Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
516	130	151	110	0.83	1.97	4.69	1.18	1.37

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		<b>CECOMAF</b> Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	374	94	110	49	0.75	1.20	7.46	1.88	2.18
-30	(-22)	502	126	147	72	0.78	1.61	7.23	1.82	2.12
-25	(-13)	654	165	192	91	0.81	2.10	7.36	1.85	2.16
-20	(- 4)	838	211	245	108	0.85	2.69	7.84	1.98	2.30
-15	(+ 5)	1063	268	311	123	0.89	3.42	8.65	2.18	2.53
-10	(+14)	1338	337	392	136	0.93	4.31	9.78	2.46	2.87

TEST CONDITIONS: @220V50Hz		<b>CECOMAF</b> Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	343	86	100	72	0.77	1.19	4.97	1.25	1.46
-30	(-22)	453	114	133	89	0.79	1.58	5.13	1.29	1.50
-25	(-13)	584	147	171	104	0.82	2.03	5.54	1.40	1.62
-20	(- 4)	742	187	217	118	0.86	2.59	6.18	1.56	1.81
-15	(+ 5)	938	236	275	131	0.91	3.27	7.04	1.77	2.06
-10	(+14)	1180	297	346	144	0.96	4.13	8.10	2.04	2.37

TEST CONDITIONS: @220V50Hz		<b>CECOMAF</b> Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	301	76	88	83	0.77	1.15	3.59	0.90	1.05
-30	(-22)	397	100	116	97	0.79	1.51	3.97	1.00	1.16
-25	(-13)	507	128	149	110	0.83	1.93	4.47	1.13	1.31
-20	(- 4)	642	162	188	124	0.87	2.45	5.10	1.28	1.49
-15	(+ 5)	810	204	237	139	0.93	3.10	5.82	1.47	1.71
-10	(+14)	1020	257	299	155	1.00	3.92	6.64	1.67	1.95

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		CECOMAF Static			(Condensing temperature 65°C (+149°F) )					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	252	63	74	82	0.77	1.07	3.03	0.76	0.89
-30	(-22)	334	84	98	96	0.80	1.40	3.44	0.87	1.01
-25	(-13)	427	108	125	112	0.84	1.80	3.86	0.97	1.13
-20	(- 4)	540	136	158	129	0.90	2.29	4.29	1.08	1.26
-15	(+ 5)	682	172	200	148	0.97	2.90	4.71	1.19	1.38
-10	(+14)	862	217	253	170	1.06	3.68	5.10	1.29	1.50

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		