

COMPRESSOR DEFINITION

Designation	NE K2140Z
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	269GG92

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Low Back Pressure R134a		
4.1 Evaporating temperature range	-30°C to -5°C	(-22°F to 23°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/2	[hp]
2 Displacement	16.80	[cm ³] (1.025 cu.in)
2.1 Bore [mm]	31.190	
2.2 Stroke [mm]	22.000	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	11	[kg] (24.25 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH-68-31	
3 Start capacitor	189-227(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0793/J5	
6 Start winding resistance	6.54	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.89	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	40.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1706	430	500	420	5.97	9.69	4.06	1.02	1.19

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-30	(-22)	1273	321	373	328	5.55	7.21	3.89	0.98	1.14
-25	(-13)	1729	436	507	375	5.74	9.82	4.61	1.16	1.35
-20	(- 4)	2279	574	668	427	6.01	12.97	5.33	1.34	1.56
-15	(+ 5)	2929	738	858	486	6.36	16.72	6.03	1.52	1.77
-10	(+14)	3686	929	1080	551	6.79	21.12	6.70	1.69	1.96
-5	(+23)	4555	1148	1335	621	7.29	26.20	7.33	1.85	2.15

TEST CONDITIONS: @115V60Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-30	(-22)	1201	303	352	332	5.54	6.81	3.62	0.91	1.06
-25	(-13)	1625	410	476	386	5.78	9.23	4.21	1.06	1.23
-20	(- 4)	2148	541	629	448	6.11	12.23	4.80	1.21	1.41
-15	(+ 5)	2776	700	813	516	6.53	15.85	5.38	1.35	1.58
-10	(+14)	3515	886	1030	592	7.03	20.13	5.94	1.50	1.74
-5	(+23)	4370	1101	1281	675	7.63	25.14	6.47	1.63	1.90

TEST CONDITIONS: @115V60Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-30	(-22)	1134	286	332	337	5.56	6.43	3.36	0.85	0.98
-25	(-13)	1526	385	447	397	5.84	8.67	3.85	0.97	1.13
-20	(- 4)	2022	509	592	466	6.23	11.51	4.34	1.09	1.27
-15	(+ 5)	2626	662	770	543	6.71	14.99	4.84	1.22	1.42
-10	(+14)	3347	843	981	629	7.29	19.17	5.32	1.34	1.56
-5	(+23)	4188	1055	1227	723	7.98	24.09	5.79	1.46	1.70

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.1 +0.10/+0.00	[mm]	(0.319" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.45 +0.10/+0.00	[mm]	(0.254" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		