

COMPRESSOR DEFINITION

Designation	EG X90CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513703056

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	12.21	[cm ³] (0.745 cu.in)
2.1 Bore [mm]	26.000	
2.2 Stroke [mm]	23.000	
3 Lubricant charge	280	[ml] (9.47 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	11.05	[kg] (24.36 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17C3/8EA5B3/QPS2-A22MD3/QPS2-A22MD3 091	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(380)	[µF(VAC minimum)]
5 Motor protection	4TM189NFBYY-53	
6 Start winding resistance	22.45	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	18.35	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	5.10	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.85	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
560	141	164	112	0.51	2.14	4.99	1.26	1.46

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	389	98	114	81	0.38	1.35	4.78	1.20	1.40
-30 (-22)	505	127	148	93	0.43	1.76	5.45	1.37	1.60
-25 (-13)	645	163	189	105	0.48	2.25	6.18	1.56	1.81
-20 (- 4)	817	206	239	117	0.53	2.85	6.99	1.76	2.05
-15 (+ 5)	1028	259	301	130	0.58	3.59	7.88	1.99	2.31
-10 (+14)	1289	325	378	145	0.65	4.51	8.87	2.24	2.60

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	328	83	96	85	0.39	1.24	3.87	0.97	1.13
-30 (-22)	435	110	127	99	0.45	1.66	4.42	1.11	1.30
-25 (-13)	560	141	164	112	0.51	2.14	5.00	1.26	1.46
-20 (- 4)	710	179	208	127	0.57	2.71	5.61	1.41	1.64
-15 (+ 5)	894	225	262	142	0.63	3.42	6.28	1.58	1.84
-10 (+14)	1121	282	328	159	0.71	4.30	7.01	1.77	2.05

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	274	69	80	86	0.39	1.16	3.20	0.81	0.94
-30 (-22)	374	94	109	101	0.46	1.57	3.68	0.93	1.08
-25 (-13)	484	122	142	116	0.53	2.04	4.15	1.05	1.22
-20 (- 4)	614	155	180	133	0.60	2.60	4.62	1.16	1.35
-15 (+ 5)	772	195	226	151	0.68	3.28	5.11	1.29	1.50
-10 (+14)	966	243	283	172	0.77	4.12	5.63	1.42	1.65

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	8.2 +0.12/-0.08	[mm]	(0.323" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		