

COMPRESSOR DEFINITION

Designation	NT 6220GKV
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	922JD04

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.50	[cm ³] (0.885 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	15.870	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	16.9	[kg] (37.26 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA4AL3C-649	
3 Start capacitor	72-88(330)	[µF(VAC minimum)]
4 Run capacitor	15(440)	[µF(VAC minimum)]
5 Motor protection	T0590/G9	
6 Start winding resistance	6.49	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.69	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	26.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

E - PERFORMANCE - CURVES

TEST CONDITIONS: @208V60Hz		ARI4 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3292	830	965	579	2.81	27.74	5.68	1.43	1.67
-15	(+ 5)	4153	1047	1217	637	3.10	35.55	6.52	1.64	1.91
-10	(+14)	5115	1289	1499	693	3.38	44.30	7.38	1.86	2.16
-5	(+23)	6204	1563	1818	749	3.66	54.46	8.29	2.09	2.43
0	(+32)	7450	1877	2183	804	3.94	66.50	9.27	2.34	2.72
+5	(+41)	8878	2237	2602	858	4.21	80.88	10.34	2.61	3.03
+10	(+50)	10518	2651	3082	912	4.48	98.07	11.53	2.91	3.38

TEST CONDITIONS: @208V60Hz		ARI4 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2666	672	781	612	2.98	26.05	4.37	1.10	1.28
-15	(+ 5)	3399	857	996	681	3.33	33.59	4.99	1.26	1.46
-10	(+14)	4207	1060	1233	749	3.67	42.12	5.62	1.42	1.65
-5	(+23)	5117	1289	1499	816	4.00	52.11	6.27	1.58	1.84
0	(+32)	6157	1552	1804	882	4.33	64.03	6.98	1.76	2.04
+5	(+41)	7356	1854	2155	948	4.66	78.35	7.75	1.95	2.27
+10	(+50)	8740	2203	2561	1014	4.99	95.53	8.63	2.17	2.53

TEST CONDITIONS: @208V60Hz		ARI4 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2007	506	588	641	3.11	23.65	3.13	0.79	0.92
-15	(+ 5)	2589	652	759	724	3.52	30.77	3.57	0.90	1.05
-10	(+14)	3220	811	944	806	3.94	38.93	4.00	1.01	1.17
-5	(+23)	3928	990	1151	888	4.34	48.61	4.43	1.12	1.30
0	(+32)	4741	1195	1389	969	4.75	60.27	4.90	1.23	1.43
+5	(+41)	5687	1433	1666	1049	5.15	74.38	5.42	1.36	1.59
+10	(+50)	6793	1712	1990	1130	5.55	91.41	6.01	1.51	1.76

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		