

COMPRESSOR DEFINITION

Designation	NT 2192GK
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	923EG02

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1 1/4	[hp]
2 Displacement	22.37	[cm ³] (1.365 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	20.830	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17.5	[kg] (38.58 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA2AE3D-660	
3 Start capacitor	243-292(165)	[µF(VAC minimum)]
4 Run capacitor	35(440)	[µF(VAC minimum)]
5 Motor protection	CRA1773	
6 Start winding resistance	2.59	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.34	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ARILBP Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 48.9°C (120.02°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3219	811	943	922	8.77	33.32	3.49	0.88	1.02

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ARI4 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1621	408	475	517	5.44	13.31	3.13	0.79	0.92
-35	(-31)	2294	578	672	626	6.30	19.01	3.66	0.92	1.07
-30	(-22)	3118	786	914	732	7.16	25.98	4.26	1.07	1.25
-25	(-13)	4087	1030	1198	836	8.02	34.29	4.90	1.23	1.44
-20	(- 4)	5197	1310	1523	936	8.87	43.95	5.57	1.40	1.63
-15	(+ 5)	6441	1623	1887	1034	9.72	55.03	6.24	1.57	1.83
-10	(+14)	7815	1969	2290	1129	10.56	67.55	6.90	1.74	2.02

TEST CONDITIONS: @115V60Hz			ARI4 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1314	331	385	540	5.63	12.50	2.46	0.62	0.72
-35	(-31)	1825	460	535	646	6.46	17.39	2.83	0.71	0.83
-30	(-22)	2481	625	727	756	7.36	23.75	3.26	0.82	0.96
-25	(-13)	3277	826	960	870	8.32	31.62	3.74	0.94	1.10
-20	(- 4)	4207	1060	1233	989	9.34	41.03	4.24	1.07	1.24
-15	(+ 5)	5267	1327	1543	1111	10.42	52.03	4.74	1.20	1.39
-10	(+14)	6450	1625	1890	1238	11.57	64.67	5.23	1.32	1.53

TEST CONDITIONS: @115V60Hz			ARI4 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1097	277	322	565	5.83	12.40	1.92	0.48	0.56
-35	(-31)	1401	353	411	663	6.61	15.99	2.13	0.54	0.62
-30	(-22)	1845	465	541	773	7.52	21.22	2.40	0.61	0.70
-25	(-13)	2423	610	710	894	8.56	28.14	2.71	0.68	0.80
-20	(- 4)	3129	788	917	1026	9.73	36.78	3.05	0.77	0.89
-15	(+ 5)	3959	998	1160	1169	11.03	47.20	3.38	0.85	0.99
-10	(+14)	4907	1237	1438	1323	12.46	59.42	3.70	0.93	1.08

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		