

COMPRESSOR DEFINITION

Designation	NE K1118Z
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	268FA47

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR-RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	8.39	[cm ³] (0.512 cu.in)
2.1 Bore [mm]	24.282	
2.2 Stroke [mm]	18.120	
3 Lubricant charge	350	[ml] (11.84 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	10.7	[kg] (23.59 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(450)	[µF(VAC minimum)]
5 Motor protection	AD58FJ10	
6 Start winding resistance	16.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	11.00	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	6.90	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.94	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
766	193	224	157	0.74	4.35	4.88	1.23	1.43

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	431	109	126	103	0.50	2.44	4.18	1.05	1.22
-30	(-22)	593	149	174	119	0.57	3.36	4.96	1.25	1.45
-25	(-13)	789	199	231	138	0.64	4.48	5.73	1.44	1.68
-20	(- 4)	1027	259	301	158	0.72	5.85	6.52	1.64	1.91
-15	(+ 5)	1313	331	385	179	0.81	7.50	7.36	1.85	2.16
-10	(+14)	1655	417	485	200	0.91	9.48	8.27	2.08	2.42

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	390	98	114	103	0.50	2.21	3.81	0.96	1.12
-30	(-22)	550	139	161	122	0.58	3.12	4.51	1.14	1.32
-25	(-13)	743	187	218	143	0.66	4.22	5.18	1.31	1.52
-20	(- 4)	976	246	286	167	0.76	5.56	5.85	1.48	1.72
-15	(+ 5)	1256	316	368	191	0.86	7.17	6.56	1.65	1.92
-10	(+14)	1589	400	466	217	0.98	9.10	7.32	1.84	2.14

TEST CONDITIONS: @220V50Hz		ASHRAE32 Static				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	350	88	103	101	0.50	1.98	3.47	0.88	1.02
-30	(-22)	505	127	148	123	0.59	2.86	4.09	1.03	1.20
-25	(-13)	691	174	203	148	0.68	3.92	4.68	1.18	1.37
-20	(- 4)	916	231	268	175	0.79	5.21	5.24	1.32	1.54
-15	(+ 5)	1185	299	347	203	0.92	6.76	5.83	1.47	1.71
-10	(+14)	1506	379	441	233	1.05	8.63	6.45	1.63	1.89

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.86 +0.07/+0.00	[mm]	(0.191" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		