

### COMPRESSOR DEFINITION

Designation	<b>EM X32CLC</b>
Nominal Voltage/Frequency	<b>220-240 V 50 Hz</b>
Engineering Number	<b>875CA95</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 154 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm <sup>2</sup> ] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm <sup>2</sup> ] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.96	[cm <sup>3</sup> ] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.5	[kg] (16.53 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD3-220V	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	4(440)	[μF(VAC minimum)]
5 Motor protection	4TM110NFBYY-53	
6 Start winding resistance	24.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	51.50	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
247	62	72	54	0.27	0.94	4.60	1.16	1.35

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	171	43	50	40	0.21	0.60	4.28	1.08	1.26
-30	(-22)	225	57	66	46	0.23	0.78	4.95	1.25	1.45
-25	(-13)	295	74	87	52	0.26	1.03	5.63	1.42	1.65
-20	(- 4)	382	96	112	60	0.29	1.33	6.35	1.60	1.86
-15	(+ 5)	486	123	142	68	0.32	1.70	7.15	1.80	2.10
-10	(+14)	608	153	178	76	0.36	2.13	8.05	2.03	2.36

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	134	34	39	39	0.21	0.51	3.44	0.87	1.01
-30	(-22)	184	46	54	45	0.24	0.70	4.04	1.02	1.18
-25	(-13)	247	62	72	53	0.27	0.94	4.60	1.16	1.35
-20	(- 4)	325	82	95	63	0.30	1.24	5.16	1.30	1.51
-15	(+ 5)	419	106	123	73	0.34	1.60	5.73	1.44	1.68
-10	(+14)	527	133	155	83	0.38	2.02	6.35	1.60	1.86

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	103	26	30	39	0.21	0.44	2.64	0.66	0.77
-30	(-22)	147	37	43	46	0.24	0.62	3.22	0.81	0.94
-25	(-13)	203	51	59	55	0.27	0.86	3.72	0.94	1.09
-20	(- 4)	271	68	79	66	0.32	1.15	4.15	1.04	1.22
-15	(+ 5)	352	89	103	78	0.37	1.50	4.54	1.15	1.33
-10	(+14)	446	112	131	90	0.42	1.90	4.94	1.24	1.45

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		