

### COMPRESSOR DEFINITION

|                           |                 |
|---------------------------|-----------------|
| Designation               | EM Y20CLC       |
| Nominal Voltage/Frequency | 220-240 V 50 Hz |
| Engineering Number        | 875GA96         |

### A - APPLICATION / LIMIT WORKING CONDITIONS

|                                    |                                   |                                   |           |
|------------------------------------|-----------------------------------|-----------------------------------|-----------|
| 1 Type                             | Hermetic reciprocating compressor |                                   |           |
| 2 Refrigerant                      | R-600a                            |                                   |           |
| 3 Nominal voltage and frequency    | 220-240 / 50                      | [ V / Hz ]                        |           |
| 4 Application type                 | Low Back Pressure                 |                                   |           |
| 4.1 Evaporating temperature range  | -35°C to -10°C                    | (-31°F to 14°F)                   |           |
| 5 Motor type                       | RSIR                              |                                   |           |
| 6 Starting torque                  | LST - Low Starting Torque         |                                   |           |
| 7 Expansion device                 | Capillary tube                    |                                   |           |
| 8 Compressor cooling               | Operating voltage range           |                                   |           |
|                                    |                                   | 50 Hz                             | 60 Hz     |
| 8.1 LBP (32°C Ambient temperature) | Static                            | 198 to 254 V                      | -         |
| 8.2 LBP (43°C Ambient temperature) | Static                            | 198 to 254 V                      | -         |
| 8.3 HBP (32°C Ambient temperature) | -                                 | -                                 | -         |
| 8.4 HBP (43°C Ambient temperature) | -                                 | -                                 | -         |
| 9 Maximum condensing temperature   |                                   |                                   |           |
| 9.1 Operating                      | 6.9                               | [kgf/cm <sup>2</sup> ] (98 psig)  | / °C - °F |
| 9.2 Peak                           | 7.8                               | [kgf/cm <sup>2</sup> ] (111 psig) | / °C - °F |
| 10 Maximum winding temperature     | 130                               | [ °C ]                            |           |

### B - MECHANICAL DATA

|                               |                |                                  |
|-------------------------------|----------------|----------------------------------|
| 1 Commercial designation      |                | [hp]                             |
| 2 Displacement                | 3.97           | [cm <sup>3</sup> ] (0.242 cu.in) |
| 2.1 Bore [mm]                 | 19.000         |                                  |
| 2.2 Stroke [mm]               | 14.000         |                                  |
| 3 Lubricant charge            | 180            | [ml] (6.09 fl.oz.)               |
| 3.1 Lubricants approved       |                |                                  |
| 3.2 Lubricants type/viscosity | ALQUILB / ISO5 |                                  |
| 4 Weight (with oil charge)    | 7.44           | [kg] (16.40 lb.)                 |
| 5 Nitrogen charge             | -              | [kgf/cm <sup>2</sup> ]           |

### C - ELETRICAL DATA

|  |                                    |                                    |
|--|------------------------------------|------------------------------------|
| 1 Nominal Voltage/Frequency/Number of Phases | 220-240 V 50 Hz 1 ~ (Single phase) |                                    |
| 2 Starting device type                       | PTC                                |                                    |
| 2.1 Starting device                          | V230                               |                                    |
| 3 Start capacitor                            | -                                  | [μF(VAC minimum)]                  |
| 4 Run capacitor                              | -                                  | [μF(VAC minimum)]                  |
| 5 Motor protection                           | T0879/07                           |                                    |
| 6 Start winding resistance                   | 21.06                              | [Ω at 25°C (77°F)] +/- 8%          |
| 7 Run winding resistance                     | 63.43                              | [Ω at 25°C (77°F)] +/- 8%          |
| 8 LRA - Locked rotor amperage (50 Hz)        | -                                  | [A] - Measured according to UL 984 |
| 9 FLA - Full load amperage L/MBP (50 Hz)     | -                                  | [A]                                |
| 10 FLA - Full Load Amperage HBP (50 Hz)      | -                                  | [A]                                |
| 11 Approval boards certification             | VDE                                |                                    |

### D - PERFORMANCE - CHECK POINT DATA

| TEST CONDITIONS:<br>@220V50Hz |          |     | CECOMAFLBP<br>Static        |                               | Evaporating temperature<br>(Condensing temperature |                           | -25°C (-13°F)<br>55°C (131°F)) |       |
|-------------------------------|----------|-----|-----------------------------|-------------------------------|--|---------------------------|--------------------------------|-------|
| Cooling capacity<br>+/- 5%    |          |     | Power consumption<br>+/- 5% | Current consumption<br>+/- 5% | Gas flow rate<br>+/- 5%                            | EFFICIENCY RATE<br>+/- 7% |                                |       |
| [Btu/h]                       | [kcal/h] | [W] | [W]                         | [A]                           | [kg/h]   | [Btu/Wh]                  | [kcal/Wh]                      | [W/W] |
| 154                           | 39       | 45  | 41                          | 0.28                          | 0.59   | 3.76                      | 0.95                           | 1.10  |

### E - PERFORMANCE - CURVES

| TEST CONDITIONS:<br>@220V50Hz |       |                            | CECOMAF<br>Static |     | (Condensing temperature 45°C (+113°F)) |                               |                         |                           |           |       |
|-------------------------------|-------|----------------------------|-------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature       |       | Cooling capacity<br>+/- 5% |                   |     | Power consumption<br>+/- 5%            | Current consumption<br>+/- 5% | Gas flow rate<br>+/- 5% | EFFICIENCY RATE<br>+/- 7% |           |       |
| °C                            | (°F)  | [Btu/h]                    | [kcal/h]          | [W] | [W]                                    | [A]                           | [kg/h]                  | [Btu/Wh]                  | [kcal/Wh] | [W/W] |
| -35                           | (-31) | 101                        | 25                | 30  | 31                                     | 0.26                          | 0.35                    | 3.24                      | 0.82      | 0.95  |
| -30                           | (-22) | 136                        | 34                | 40  | 35                                     | 0.27                          | 0.47                    | 3.88                      | 0.98      | 1.14  |
| -25                           | (-13) | 183                        | 46                | 54  | 40                                     | 0.28                          | 0.64                    | 4.58                      | 1.15      | 1.34  |
| -20                           | (- 4) | 242                        | 61                | 71  | 45                                     | 0.30                          | 0.84                    | 5.33                      | 1.34      | 1.56  |
| -15                           | (+ 5) | 313                        | 79                | 92  | 51                                     | 0.32                          | 1.10                    | 6.12                      | 1.54      | 1.79  |
| -10                           | (+14) | 397                        | 100               | 116 | 57                                     | 0.34                          | 1.39                    | 6.93                      | 1.75      | 2.03  |

| TEST CONDITIONS:<br>@220V50Hz |       |                            | CECOMAF<br>Static |     | (Condensing temperature 55°C (+131°F)) |                               |                         |                           |           |       |
|-------------------------------|-------|----------------------------|-------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature       |       | Cooling capacity<br>+/- 5% |                   |     | Power consumption<br>+/- 5%            | Current consumption<br>+/- 5% | Gas flow rate<br>+/- 5% | EFFICIENCY RATE<br>+/- 7% |           |       |
| °C                            | (°F)  | [Btu/h]                    | [kcal/h]          | [W] | [W]                                    | [A]                           | [kg/h]                  | [Btu/Wh]                  | [kcal/Wh] | [W/W] |
| -35                           | (-31) | 85                         | 21                | 25  | 31                                     | 0.26                          | 0.32                    | 2.71                      | 0.68      | 0.79  |
| -30                           | (-22) | 115                        | 29                | 34  | 36                                     | 0.26                          | 0.44                    | 3.21                      | 0.81      | 0.94  |
| -25                           | (-13) | 155                        | 39                | 45  | 41                                     | 0.28                          | 0.59                    | 3.75                      | 0.95      | 1.10  |
| -20                           | (- 4) | 204                        | 52                | 60  | 47                                     | 0.30                          | 0.78                    | 4.32                      | 1.09      | 1.27  |
| -15                           | (+ 5) | 264                        | 67                | 77  | 54                                     | 0.33                          | 1.01                    | 4.90                      | 1.23      | 1.43  |
| -10                           | (+14) | 334                        | 84                | 98  | 61                                     | 0.36                          | 1.28                    | 5.47                      | 1.38      | 1.60  |

| TEST CONDITIONS:<br>@220V50Hz |       |                            | CECOMAF<br>Static |     | (Condensing temperature 65°C (+149°F)) |                               |                         |                           |           |       |
|-------------------------------|-------|----------------------------|-------------------|-----|--|-------------------------------|-------------------------|---------------------------|-----------|-------|
| Evaporating temperature       |       | Cooling capacity<br>+/- 5% |                   |     | Power consumption<br>+/- 5%            | Current consumption<br>+/- 5% | Gas flow rate<br>+/- 5% | EFFICIENCY RATE<br>+/- 7% |           |       |
| °C                            | (°F)  | [Btu/h]                    | [kcal/h]          | [W] | [W]                                    | [A]                           | [kg/h]                  | [Btu/Wh]                  | [kcal/Wh] | [W/W] |
| -35                           | (-31) | 63                         | 16                | 19  | 31                                     | 0.26                          | 0.27                    | 2.08                      | 0.52      | 0.61  |
| -30                           | (-22) | 91                         | 23                | 27  | 36                                     | 0.26                          | 0.39                    | 2.53                      | 0.64      | 0.74  |
| -25                           | (-13) | 127                        | 32                | 37  | 42                                     | 0.28                          | 0.54                    | 3.00                      | 0.76      | 0.88  |
| -20                           | (- 4) | 170                        | 43                | 50  | 49                                     | 0.31                          | 0.72                    | 3.46                      | 0.87      | 1.01  |
| -15                           | (+ 5) | 221                        | 56                | 65  | 57                                     | 0.34                          | 0.94                    | 3.91                      | 0.99      | 1.15  |
| -10                           | (+14) | 281                        | 71                | 82  | 65                                     | 0.38                          | 1.20                    | 4.33                      | 1.09      | 1.27  |

### F - EXTERNAL CHARACTERISTICS

|                         |                   |      |                          |
|-------------------------|-------------------|------|--------------------------|
| 1 Base plate            | European Standard |      |                          |
| 2 Tray holder           | No                |      |                          |
| 3 Connectors            |                   |      |                          |
| 3.1 SUCTION             | 6.1 +0.10/+0.00   | [mm] | (0.240" +0.004"/+0.000") |
| 3.1.1 Material          | Copper            |      |                          |
| 3.1.2 Shape             | Slanted 42°       |      |                          |
| 3.2 DISCHARGE           | 5.1 +0.10/+0.00   | [mm] | (0.201" +0.004"/+0.000") |
| 3.2.1 Material          | Copper            |      |                          |
| 3.2.2 Shape             | Straight          |      |                          |
| 3.3 PROCESS             | 6 +0.08/-0.08     | [mm] | (0.236" +0.003"/-0.003") |
| 3.3.1 Material          | Copper(OD)        |      |                          |
| 3.3.2 Shape             | Slanted 42°       |      |                          |
| 3.4 Oil cooler (Copper) | No                | [mm] |                          |
| 3.5 Connector sealing   | Rubber Plugs      |      |                          |