

COMPRESSOR DEFINITION

Designation	EM X20CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	875AA90

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	3.97	[cm ³] (0.242 cu.in)
2.1 Bore [mm]	19.000	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.5	[kg] (16.53 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD3-220V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	3(440)	[µF(VAC minimum)]
5 Motor protection	4TM110KFBYY-73	
6 Start winding resistance	21.50	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	67.22	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			CECOMAFLBP Static		Evaporating temperature (Condensing temperature		-25°C (-13°F) 55°C (131°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
155	39	45	37	0.19	0.59	4.22	1.06	1.24

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	99	25	29	27	0.13	0.34	3.65	0.92	1.07
-30	(-22)	141	35	41	31	0.15	0.49	4.53	1.14	1.33
-25	(-13)	188	47	55	36	0.17	0.65	5.30	1.34	1.55
-20	(- 4)	243	61	71	40	0.19	0.85	6.06	1.53	1.77
-15	(+ 5)	311	78	91	45	0.21	1.08	6.86	1.73	2.01
-10	(+14)	393	99	115	50	0.23	1.37	7.80	1.97	2.28

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	70	18	20	27	0.13	0.26	2.61	0.66	0.76
-30	(-22)	111	28	33	31	0.16	0.42	3.50	0.88	1.02
-25	(-13)	155	39	45	37	0.18	0.59	4.22	1.06	1.24
-20	(- 4)	204	52	60	42	0.20	0.78	4.85	1.22	1.42
-15	(+ 5)	263	66	77	48	0.22	1.01	5.47	1.38	1.60
-10	(+14)	333	84	98	54	0.25	1.28	6.15	1.55	1.80

TEST CONDITIONS: @220V50Hz			CECOMAF Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	43	11	13	25	0.13	0.18	1.71	0.43	0.50
-30	(-22)	85	21	25	31	0.16	0.36	2.65	0.67	0.78
-25	(-13)	127	32	37	37	0.18	0.53	3.36	0.85	0.99
-20	(- 4)	171	43	50	44	0.20	0.72	3.91	0.99	1.15
-15	(+ 5)	222	56	65	51	0.23	0.94	4.39	1.11	1.29
-10	(+14)	281	71	82	58	0.26	1.20	4.85	1.22	1.42

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		