

COMPRESSOR DEFINITION

Designation	EM U32CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	895LA90

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	5.96	[cm ³] (0.364 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	15.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	6.8	[kg] (14.99 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	AE24AHN10	
6 Start winding resistance	25.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	36.20	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	2.90	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.50	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
330	83	97	71	0.52	1.04	4.67	1.18	1.37

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	176	44	52	50	0.47	0.55	3.52	0.89	1.03
-30	(-22)	245	62	72	57	0.48	0.77	4.28	1.08	1.25
-25	(-13)	329	83	96	65	0.49	1.03	5.02	1.27	1.47
-20	(- 4)	427	108	125	74	0.50	1.34	5.78	1.46	1.69
-15	(+ 5)	541	136	158	82	0.52	1.70	6.60	1.66	1.93
-10	(+14)	670	169	196	89	0.54	2.11	7.51	1.89	2.20

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	157	40	46	50	0.47	0.49	3.11	0.78	0.91
-30	(-22)	220	55	64	58	0.48	0.69	3.78	0.95	1.11
-25	(-13)	298	75	87	68	0.50	0.94	4.42	1.11	1.29
-20	(- 4)	391	99	115	77	0.52	1.23	5.05	1.27	1.48
-15	(+ 5)	500	126	146	87	0.54	1.57	5.73	1.44	1.68
-10	(+14)	624	157	183	96	0.56	1.97	6.48	1.63	1.90

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	130	33	38	50	0.47	0.41	2.61	0.66	0.76
-30	(-22)	191	48	56	59	0.49	0.60	3.25	0.82	0.95
-25	(-13)	266	67	78	70	0.51	0.84	3.84	0.97	1.12
-20	(- 4)	357	90	105	81	0.53	1.12	4.40	1.11	1.29
-15	(+ 5)	464	117	136	93	0.55	1.46	4.99	1.26	1.46
-10	(+14)	587	148	172	104	0.58	1.85	5.62	1.42	1.65

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		