

COMPRESSOR DEFINITION

Designation	EM Y75HLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	513300215

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling		Operating voltage range	
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	187 to 255 V	-
8.2 LBP (43°C Ambient temperature)	Static	187 to 255 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	6.99	[cm ³] (0.427 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	17.600	
3 Lubricant charge	150	[ml] (5.07 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO7	
4 Weight (with oil charge)	7.4	[kg] (16.31 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA17B3	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	4(300)	[µF(VAC minimum)]
5 Motor protection	4TM232NFBYY-53	
6 Start winding resistance	19.85	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	13.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	7.75	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	1.09	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CCC - VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
734	185	215	134	0.68	4.17	5.46	1.38	1.60

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	386	97	113	93	0.50	2.19	4.16	1.05	1.22
-30 (-22)	543	137	159	106	0.56	3.08	5.09	1.28	1.49
-25 (-13)	716	180	210	121	0.62	4.07	5.93	1.49	1.74
-20 (- 4)	917	231	269	137	0.69	5.22	6.68	1.68	1.96
-15 (+ 5)	1154	291	338	156	0.77	6.59	7.39	1.86	2.17
-10 (+14)	1438	362	421	178	0.87	8.24	8.08	2.04	2.37

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	340	86	100	93	0.49	1.92	3.68	0.93	1.08
-30 (-22)	491	124	144	110	0.57	2.79	4.44	1.12	1.30
-25 (-13)	661	167	194	129	0.65	3.75	5.14	1.30	1.51
-20 (- 4)	859	216	252	148	0.73	4.89	5.80	1.46	1.70
-15 (+ 5)	1095	276	321	170	0.82	6.25	6.44	1.62	1.89
-10 (+14)	1379	348	404	194	0.93	7.90	7.10	1.79	2.08

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	302	76	89	89	0.48	1.71	3.41	0.86	1.00
-30 (-22)	441	111	129	110	0.57	2.50	4.00	1.01	1.17
-25 (-13)	600	151	176	132	0.66	3.41	4.56	1.15	1.34
-20 (- 4)	788	199	231	154	0.76	4.48	5.11	1.29	1.50
-15 (+ 5)	1016	256	298	178	0.86	5.80	5.68	1.43	1.67
-10 (+14)	1294	326	379	204	0.97	7.41	6.31	1.59	1.85

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard EUEM		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 0° up + 45° to Back		
3.2 DISCHARGE	4.9 +0.10/-0.05	[mm]	(0.193" +0.004"/-0.002")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted 0° up + 24° to Back		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 40° up + 45° to Back		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		