

### COMPRESSOR DEFINITION

Designation	EM T43HLP
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	192DA47

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	4.85	[cm <sup>3</sup> ] (0.296 cu.in)
2.1 Bore [mm]	21.000	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	7.52	[kg] (16.58 lb.)
5 Nitrogen charge	-	[kgf/cm <sup>2</sup> ]

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	V230	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	T0225/G6	
6 Start winding resistance	23.70	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	22.30	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	IMQ	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900LBP_HH Static		Evaporating temperature (Condensing temperature		-35°C (-31°F) 40°C (104°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
244	61	71	71	0.63		3.44	0.87	1.01

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			EN12900HH Static		(Condensing temperature 35°C (+95°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	261	66	76	71	0.64	- 0.03	3.69	0.93	1.08
-30 (-22)	363	92	107	80	0.66	- 0.88	4.53	1.14	1.33
-25 (-13)	481	121	141	90	0.68	0.09	5.33	1.34	1.56
-20 (- 4)	620	156	182	101	0.71	2.13	6.13	1.54	1.80
-15 (+ 5)	786	198	230	113	0.75	4.50	6.99	1.76	2.05
-10 (+14)	984	248	288	124	0.78	6.45	7.96	2.01	2.33

TEST CONDITIONS: @220V50Hz			EN12900HH Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	217	55	64	71	0.64	0.00	3.08	0.78	0.90
-30 (-22)	304	76	89	81	0.66	- 0.91	3.74	0.94	1.10
-25 (-13)	403	102	118	93	0.69	0.00	4.33	1.09	1.27
-20 (- 4)	522	132	153	106	0.73	1.96	4.91	1.24	1.44
-15 (+ 5)	666	168	195	120	0.77	4.25	5.53	1.39	1.62
-10 (+14)	840	212	246	134	0.82	6.10	6.25	1.58	1.83

TEST CONDITIONS: @220V50Hz			EN12900HH Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	182	46	53	71	0.64	0.03	2.57	0.65	0.75
-30 (-22)	253	64	74	82	0.66	- 0.93	3.09	0.78	0.90
-25 (-13)	335	85	98	96	0.70	- 0.09	3.52	0.89	1.03
-20 (- 4)	435	110	127	111	0.74	1.81	3.94	0.99	1.15
-15 (+ 5)	558	141	163	127	0.79	4.01	4.37	1.10	1.28
-10 (+14)	709	179	208	144	0.85	5.77	4.89	1.23	1.43

### F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Slanted parallel to Base Plate		
3.3 PROCESS	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		