

COMPRESSOR DEFINITION

Designation	NT 6222GK
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	922CD04

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	17.39	[cm ³] (1.061 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17.2	[kg] (37.92 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA4AL3C-649	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	15(440)	[µF(VAC minimum)]
5 Motor protection	T0808/G9	
6 Start winding resistance	6.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.58	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @230V60Hz			ARIMBP Fan		Evaporating temperature (Condensing temperature		-6.7°C (19.94°F) 48.9°C (120.02°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
5241	1321	1536	1099	5.02	56.48	4.77	1.20	1.40

E - PERFORMANCE - CURVES

TEST CONDITIONS: @230V60Hz		ARI4 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3992	1006	1170	807	3.61	29.84	4.94	1.24	1.45
-15	(+ 5)	5040	1270	1477	880	4.00	48.09	5.72	1.44	1.68
-10	(+14)	6227	1569	1825	951	4.35	60.37	6.55	1.65	1.92
-5	(+23)	7553	1903	2213	1020	4.66	63.67	7.41	1.87	2.17
0	(+32)	9018	2273	2642	1087	4.97	54.96	8.30	2.09	2.43
+5	(+41)	10621	2676	3112	1152	5.26	31.24	9.22	2.32	2.70
+10	(+50)	12361	3115	3622	1215	5.57	- 10.52	10.16	2.56	2.98

TEST CONDITIONS: @230V60Hz		ARI4 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3213	810	942	835	3.68	28.35	3.86	0.97	1.13
-15	(+ 5)	4102	1034	1202	929	4.09	45.56	4.42	1.11	1.29
-10	(+14)	5126	1292	1502	1020	4.47	57.39	5.02	1.27	1.47
-5	(+23)	6284	1584	1841	1106	4.84	60.80	5.67	1.43	1.66
0	(+32)	7576	1909	2220	1190	5.19	52.79	6.36	1.60	1.86
+5	(+41)	9001	2268	2638	1269	5.56	30.33	7.09	1.79	2.08
+10	(+50)	10560	2661	3094	1346	5.94	- 9.58	7.85	1.98	2.30

TEST CONDITIONS: @230V60Hz		ARI4 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2406	606	705	865	4.04	24.48	2.77	0.70	0.81
-15	(+ 5)	3048	768	893	973	4.49	40.92	3.13	0.79	0.92
-10	(+14)	3820	963	1119	1076	4.92	52.55	3.55	0.90	1.04
-5	(+23)	4722	1190	1384	1173	5.34	56.34	4.02	1.01	1.18
0	(+32)	5753	1450	1686	1265	5.77	49.29	4.55	1.15	1.33
+5	(+41)	6913	1742	2026	1353	6.21	28.38	5.11	1.29	1.50
+10	(+50)	8202	2067	2403	1435	6.69	- 9.42	5.72	1.44	1.68

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		