

### COMPRESSOR DEFINITION

Designation	<b>NT 6226GKV</b>
Nominal Voltage/Frequency	<b>220-240 V 50 Hz</b>
Engineering Number	<b>923AA02</b>

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm <sup>2</sup> ] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm <sup>2</sup> ] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	22.37	[cm <sup>3</sup> ] (1.365 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	20.830	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17.5	[kg] (38.58 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA403C-123	
3 Start capacitor	130-156(250)	[μF(VAC minimum)]
4 Run capacitor	20(400)	[μF(VAC minimum)]
5 Motor protection	T0828/C9	
6 Start winding resistance	8.40	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			EN12900MBP Fan		Evaporating temperature (Condensing temperature		-10°C (14°F) 45°C (113°F))	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
5978	1506	1752	980	4.78	52.62	6.10	1.54	1.79

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	4647	1171	1362	764	3.83	35.28	6.07	1.53	1.78
-15	(+ 5)	5820	1467	1705	831	4.12	44.61	7.01	1.77	2.05
-10	(+14)	7214	1818	2114	898	4.42	55.75	8.04	2.03	2.36
-5	(+23)	8831	2225	2588	966	4.72	68.91	9.14	2.30	2.68
0	(+32)	10670	2689	3127	1034	5.03	84.31	10.31	2.60	3.02
+5	(+41)	12731	3208	3730	1104	5.35	102.18	11.53	2.91	3.38
+10	(+50)	15014	3783	4399	1175	5.67	122.72	12.79	3.22	3.75

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3784	953	1109	820	4.08	32.67	4.62	1.16	1.35
-15	(+ 5)	4795	1208	1405	901	4.43	41.82	5.33	1.34	1.56
-10	(+14)	5991	1510	1755	980	4.78	52.72	6.11	1.54	1.79
-5	(+23)	7369	1857	2159	1060	5.14	65.61	6.95	1.75	2.04
0	(+32)	8931	2251	2617	1139	5.49	80.70	7.84	1.98	2.30
+5	(+41)	10676	2690	3128	1218	5.86	98.20	8.77	2.21	2.57
+10	(+50)	12605	3176	3693	1296	6.23	118.33	9.72	2.45	2.85

TEST CONDITIONS: @220V50Hz			EN12900 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3077	776	902	870	4.30	31.26	3.54	0.89	1.04
-15	(+ 5)	3889	980	1140	967	4.73	39.93	4.02	1.01	1.18
-10	(+14)	4846	1221	1420	1062	5.16	50.32	4.56	1.15	1.34
-5	(+23)	5947	1499	1743	1156	5.58	62.65	5.15	1.30	1.51
0	(+32)	7192	1813	2108	1248	6.01	77.12	5.77	1.45	1.69
+5	(+41)	8583	2163	2515	1339	6.44	93.96	6.42	1.62	1.88
+10	(+50)	10118	2550	2965	1429	6.86	113.39	7.08	1.78	2.07

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		