

COMPRESSOR DEFINITION

Designation	EM Y46CLC
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	897FA95

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-600a		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSIR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	198 to 254 V	-
8.2 LBP (43°C Ambient temperature)	Static	198 to 254 V	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	6.9	[kgf/cm ²] (98 psig)	/ °C - °F
9.2 Peak	7.8	[kgf/cm ²] (111 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation		[hp]
2 Displacement	7.96	[cm ³] (0.486 cu.in)
2.1 Bore [mm]	24.000	
2.2 Stroke [mm]	17.600	
3 Lubricant charge	180	[ml] (6.09 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ALQUILB / ISO5	
4 Weight (with oil charge)	7.7	[kg] (16.98 lb.)
5 Nitrogen charge	-	[kgf/cm ²]

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	2019	
3 Start capacitor	-	[μF(VAC minimum)]
4 Run capacitor	-	[μF(VAC minimum)]
5 Motor protection	AE37FN10	
6 Start winding resistance	17.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	22.10	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	4.40	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	0.57	[A]
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A]
11 Approval boards certification	VDE	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @220V50Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
461	116	135	87	0.59	1.45	5.32	1.34	1.56

E - PERFORMANCE - CURVES

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	228	57	67	60	0.52	0.71	3.81	0.96	1.12
-30	(-22)	323	82	95	69	0.54	1.01	4.69	1.18	1.37
-25	(-13)	439	111	129	80	0.56	1.38	5.49	1.38	1.61
-20	(- 4)	575	145	169	92	0.60	1.81	6.28	1.58	1.84
-15	(+ 5)	736	185	216	104	0.63	2.32	7.11	1.79	2.08
-10	(+14)	922	232	270	115	0.67	2.91	8.05	2.03	2.36

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	212	53	62	59	0.53	0.66	3.59	0.90	1.05
-30	(-22)	304	77	89	69	0.54	0.95	4.38	1.10	1.28
-25	(-13)	416	105	122	82	0.58	1.30	5.07	1.28	1.48
-20	(- 4)	547	138	160	96	0.62	1.72	5.71	1.44	1.67
-15	(+ 5)	702	177	206	110	0.66	2.21	6.36	1.60	1.86
-10	(+14)	882	222	258	124	0.71	2.78	7.09	1.79	2.08

TEST CONDITIONS: @220V50Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35	(-31)	188	48	55	59	0.52	0.59	3.21	0.81	0.94
-30	(-22)	283	71	83	70	0.54	0.89	4.02	1.01	1.18
-25	(-13)	395	99	116	84	0.58	1.24	4.68	1.18	1.37
-20	(- 4)	526	133	154	100	0.63	1.66	5.27	1.33	1.54
-15	(+ 5)	680	171	199	116	0.68	2.14	5.84	1.47	1.71
-10	(+14)	857	216	251	133	0.74	2.70	6.46	1.63	1.89

F - EXTERNAL CHARACTERISTICS

1 Base plate	European Standard		
2 Tray holder	Yes		
3 Connectors			
3.1 SUCTION	6.1 +0.10/+0.00	[mm]	(0.240" +0.004"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Slanted 42°		
3.2 DISCHARGE	5.1 +0.10/+0.00	[mm]	(0.201" +0.004"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6 +0.08/-0.08	[mm]	(0.236" +0.003"/-0.003")
3.3.1 Material	Copper(OD)		
3.3.2 Shape	Slanted 42°		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		