

COMPRESSOR DEFINITION

Designation	NT 6217ZV
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	212EG09

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	High Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-15°C to 10°C	(5°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	20.44	[cm ³] (1.247 cu.in)
2.1 Bore [mm]	36.990	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17.5	[kg] (38.58 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	3CR-702-282	
3 Start capacitor	243-292(250)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0865/G9	
6 Start winding resistance	2.62	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.51	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	45.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
7460	1880	2186	990	10.50	48.37	7.54	1.90	2.21

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz		ASHRAE46 Fan				(Condensing temperature 35°C (+95°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	3856	972	1130	535	7.02	20.85	7.21	1.82	2.11
-10	(+14)	4851	1222	1421	592	7.40	26.32	8.20	2.07	2.40
-5	(+23)	6025	1518	1765	650	7.81	32.82	9.26	2.33	2.71
0	(+32)	7373	1858	2161	709	8.25	40.35	10.39	2.62	3.04
+5	(+41)	8891	2241	2605	770	8.72	48.92	11.54	2.91	3.38
+10	(+50)	10573	2664	3098	833	9.21	58.54	12.71	3.20	3.72

TEST CONDITIONS: @115V60Hz		ASHRAE46 Fan				(Condensing temperature 45°C (+113°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	3371	849	988	565	7.24	19.69	5.95	1.50	1.74
-10	(+14)	4290	1081	1257	642	7.77	25.16	6.68	1.68	1.96
-5	(+23)	5357	1350	1570	716	8.30	31.55	7.48	1.89	2.19
0	(+32)	6568	1655	1924	789	8.85	38.86	8.34	2.10	2.44
+5	(+41)	7916	1995	2320	860	9.41	47.12	9.21	2.32	2.70
+10	(+50)	9399	2369	2754	930	9.97	56.31	10.10	2.55	2.96

TEST CONDITIONS: @115V60Hz		ASHRAE46 Fan				(Condensing temperature 55°C (+131°F))				
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-15	(+5)	2734	689	801	590	7.38	17.43	4.65	1.17	1.36
-10	(+14)	3595	906	1054	691	8.10	23.00	5.20	1.31	1.52
-5	(+23)	4574	1153	1340	786	8.81	29.38	5.81	1.46	1.70
0	(+32)	5665	1427	1660	875	9.51	36.58	6.47	1.63	1.90
+5	(+41)	6863	1729	2011	960	10.19	44.61	7.16	1.80	2.10
+10	(+50)	8164	2057	2392	1041	10.86	53.48	7.84	1.98	2.30

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	12.7 +0.25/-0.25	[mm]	(0.500" +0.010"/-0.010")
3.1.1 Material	Steel		
3.1.2 Shape	ROTOLOCK(Ex. thr. 1"-14UNS-2A)		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		