

### COMPRESSOR DEFINITION

Designation	NT 6220GKV
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	922JG02

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115 / 60	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm <sup>2</sup> ] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm <sup>2</sup> ] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.50	[cm <sup>3</sup> ] (0.885 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	15.870	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17	[kg] (37.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	3ARR2KCP172S	
3 Start capacitor	243-292(165)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	CRA1773	
6 Start winding resistance	2.66	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.43	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	54.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	12.58	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
8464	2133	2480	1160	12.20	69.68	7.30	1.84	2.14

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3919	988	1148	615	7.98	24.89	6.36	1.60	1.86
-15	(+ 5)	4962	1250	1454	676	8.40	31.68	7.34	1.85	2.15
-10	(+14)	6204	1563	1818	734	8.80	39.84	8.47	2.13	2.48
-5	(+23)	7642	1926	2239	787	9.19	49.43	9.72	2.45	2.85
0	(+32)	9273	2337	2717	836	9.57	60.52	11.10	2.80	3.25
+5	(+41)	11095	2796	3251	881	9.92	73.18	12.59	3.17	3.69
+10	(+50)	13106	3303	3840	922	10.27	87.48	14.20	3.58	4.16

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3243	817	950	659	8.29	22.70	4.93	1.24	1.44
-15	(+ 5)	4169	1051	1222	737	8.82	29.39	5.66	1.43	1.66
-10	(+14)	5259	1325	1541	810	9.35	37.33	6.49	1.64	1.90
-5	(+23)	6509	1640	1907	877	9.86	46.58	7.41	1.87	2.17
0	(+32)	7918	1995	2320	941	10.37	57.21	8.41	2.12	2.46
+5	(+41)	9483	2390	2779	999	10.86	69.31	9.49	2.39	2.78
+10	(+50)	11202	2823	3283	1053	11.34	82.93	10.65	2.68	3.12

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2618	660	767	679	8.42	20.59	3.86	0.97	1.13
-15	(+ 5)	3410	859	999	779	9.12	27.00	4.38	1.10	1.28
-10	(+14)	4331	1091	1269	874	9.83	34.55	4.95	1.25	1.45
-5	(+23)	5378	1355	1576	963	10.53	43.29	5.58	1.41	1.64
0	(+32)	6549	1650	1919	1048	11.22	53.31	6.25	1.58	1.83
+5	(+41)	7840	1976	2297	1126	11.90	64.66	6.96	1.75	2.04
+10	(+50)	9251	2331	2711	1200	12.57	77.43	7.71	1.94	2.26

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		