

COMPRESSOR DEFINITION

Designation	NT 2168GKV
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	922IG02

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.50	[cm ³] (0.885 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	15.870	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17	[kg] (37.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELECTRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	3ARR2KCP172S	
3 Start capacitor	243-292(165)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0873/G9	
6 Start winding resistance	2.66	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.43	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	54.50	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ARILBP Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 48.9°C (120.02°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
1983	500	581	635	8.05	20.53	3.12	0.79	0.91

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ARI4 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	879	221	257	337	6.53	7.19	2.60	0.65	0.76
-35	(-31)	1358	342	398	426	6.93	11.26	3.17	0.80	0.93
-30	(-22)	1918	483	562	508	7.34	16.00	3.78	0.95	1.11
-25	(-13)	2557	644	749	583	7.76	21.46	4.41	1.11	1.29
-20	(- 4)	3278	826	960	650	8.18	27.72	5.07	1.28	1.49
-15	(+ 5)	4078	1028	1195	710	8.61	34.84	5.76	1.45	1.69
-10	(+14)	4960	1250	1453	761	9.05	42.86	6.47	1.63	1.90

TEST CONDITIONS: @115V60Hz			ARI4 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	644	162	189	323	6.47	6.14	2.02	0.51	0.59
-35	(-31)	1009	254	296	415	6.90	9.62	2.43	0.61	0.71
-30	(-22)	1457	367	427	506	7.37	13.94	2.86	0.72	0.84
-25	(-13)	1987	501	582	596	7.89	19.16	3.31	0.83	0.97
-20	(- 4)	2599	655	762	684	8.46	25.34	3.78	0.95	1.11
-15	(+ 5)	3293	830	965	772	9.08	32.54	4.27	1.08	1.25
-10	(+14)	4070	1026	1193	858	9.75	40.82	4.78	1.20	1.40

TEST CONDITIONS: @115V60Hz			ARI4 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	556	140	163	342	6.53	6.29	1.60	0.40	0.47
-35	(-31)	781	197	229	423	6.91	8.90	1.87	0.47	0.55
-30	(-22)	1090	275	319	510	7.38	12.53	2.16	0.54	0.63
-25	(-13)	1483	374	435	602	7.94	17.22	2.47	0.62	0.72
-20	(- 4)	1960	494	574	699	8.59	23.04	2.79	0.70	0.82
-15	(+ 5)	2520	635	738	801	9.33	30.05	3.13	0.79	0.92
-10	(+14)	3164	797	927	909	10.17	38.32	3.48	0.88	1.02

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		