

COMPRESSOR DEFINITION

Designation	NT 6222GKV
Nominal Voltage/Frequency	115 V 60 Hz
Engineering Number	922KG08

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	115 / 60	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm ²] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm ²] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	17.39	[cm ³] (1.061 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17	[kg] (37.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	3ARR2KCP172S	
3 Start capacitor	340-408(165)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	CRT00AEN-376B	
6 Start winding resistance	2.60	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	0.40	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	70.00	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAEHBP46 Fan		Evaporating temperature (Condensing temperature		7.2°C (44.96°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
10376	2615	3040	1429	15.00	85.42	7.26	1.83	2.13

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	5099	1285	1494	766	9.90	32.37	6.65	1.68	1.95
-15	(+ 5)	6184	1558	1812	830	10.32	39.49	7.46	1.88	2.19
-10	(+14)	7531	1898	2207	896	10.77	48.37	8.41	2.12	2.46
-5	(+23)	9140	2303	2678	964	11.26	59.12	9.48	2.39	2.78
0	(+32)	11011	2775	3227	1033	11.78	71.85	10.65	2.69	3.12
+5	(+41)	13144	3312	3852	1103	12.34	86.68	11.91	3.00	3.49
+10	(+50)	15539	3916	4553	1176	12.93	103.72	13.22	3.33	3.87

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	4289	1081	1257	817	10.21	30.03	5.25	1.32	1.54
-15	(+ 5)	5267	1327	1543	901	10.78	37.14	5.85	1.47	1.71
-10	(+14)	6467	1630	1895	985	11.38	45.90	6.57	1.65	1.92
-5	(+23)	7887	1988	2311	1069	12.02	56.43	7.38	1.86	2.16
0	(+32)	9529	2401	2792	1153	12.68	68.85	8.26	2.08	2.42
+5	(+41)	11392	2871	3338	1238	13.37	83.26	9.21	2.32	2.70
+10	(+50)	13476	3396	3949	1322	14.10	99.77	10.19	2.57	2.99

TEST CONDITIONS: @115V60Hz			ASHRAE46 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3480	877	1020	850	10.39	27.37	4.10	1.03	1.20
-15	(+ 5)	4348	1096	1274	959	11.18	34.43	4.53	1.14	1.33
-10	(+14)	5396	1360	1581	1067	12.00	43.05	5.05	1.27	1.48
-5	(+23)	6625	1670	1941	1173	12.84	53.34	5.64	1.42	1.65
0	(+32)	8034	2025	2354	1279	13.71	65.41	6.29	1.58	1.84
+5	(+41)	9624	2425	2820	1383	14.60	79.37	6.97	1.76	2.04
+10	(+50)	11393	2871	3338	1487	15.52	95.35	7.66	1.93	2.24

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal
2 Tray holder	No
3 Connectors	
3.1 SUCTION	12.7 +0.25/-0.25 [mm] (0.500" +0.010"/-0.010")
3.1.1 Material	Steel
3.1.2 Shape	ROTOLOCK(Ex. thr. 1"-14UNS-2A)
3.2 DISCHARGE	6.42 +0.08/+0.00 [mm] (0.253" +0.003"/+0.000")
3.2.1 Material	Copper
3.2.2 Shape	Vertical
3.3 PROCESS	6.42 +0.08/+0.00 [mm] (0.253" +0.003"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Vertical
3.4 Oil cooler (Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs