

COMPRESSOR DEFINITION

Designation	EG ZS60HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513701327

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[V / Hz]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm ²] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm ²] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1/5	[hp]
2 Displacement	5.09	[cm ³] (0.311 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	12.800	
3 Lubricant charge	230	[ml] (7.78 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO10	
4 Weight (with oil charge)	11.21	[kg] (24.71 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	TSD	
2.1 Starting device	TSD- 115V	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	12(180)/15(200)/20(200)	[µF(VAC minimum)]
5 Motor protection	BT149-105	
6 Start winding resistance	6.00	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	5.15	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
595	150	174	103	0.92	3.38	5.79	1.46	1.70

E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	314	79	92	68	0.61	1.78	4.68	1.18	1.37
-30 (-22)	423	107	124	80	0.73	2.40	5.36	1.35	1.57
-25 (-13)	600	151	176	96	0.87	3.41	6.24	1.57	1.83
-20 (- 4)	833	210	244	114	1.02	4.74	7.30	1.84	2.14
-15 (+ 5)	1109	280	325	131	1.17	6.33	8.49	2.14	2.49
-10 (+14)	1417	357	415	145	1.30	8.12	9.79	2.47	2.87

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	249	63	73	60	0.56	1.41	4.08	1.03	1.20
-30 (-22)	358	90	105	75	0.69	2.03	4.79	1.21	1.40
-25 (-13)	533	134	156	95	0.85	3.02	5.62	1.42	1.65
-20 (- 4)	762	192	223	116	1.04	4.33	6.52	1.64	1.91
-15 (+ 5)	1032	260	303	138	1.24	5.89	7.47	1.88	2.19
-10 (+14)	1332	336	390	159	1.42	7.63	8.43	2.12	2.47

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	155	39	45	54	0.51	0.88	2.93	0.74	0.86
-30 (-22)	267	67	78	71	0.65	1.51	3.85	0.97	1.13
-25 (-13)	444	112	130	92	0.83	2.52	4.79	1.21	1.40
-20 (- 4)	673	170	197	117	1.04	3.83	5.72	1.44	1.68
-15 (+ 5)	942	237	276	143	1.27	5.38	6.60	1.66	1.93
-10 (+14)	1239	312	363	168	1.51	7.10	7.40	1.86	2.17

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		