

### COMPRESSOR DEFINITION

Designation	EG ZS70HLP
Nominal Voltage/Frequency	115-127 V 60 Hz
Engineering Number	513701328

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-134a		
3 Nominal voltage and frequency	115-127 / 60	[ V / Hz ]	
4 Application type	Low Back Pressure		
4.1 Evaporating temperature range	-35°C to -10°C	(-31°F to 14°F)	
5 Motor type	RSCR		
6 Starting torque	LST - Low Starting Torque		
7 Expansion device	Capillary tube		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	Static	-	98 to 140 V
8.2 LBP (43°C Ambient temperature)	Static	-	98 to 140 V
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	14.2	[kgf/cm <sup>2</sup> ] (202 psig)	/ °C - °F
9.2 Peak	15.9	[kgf/cm <sup>2</sup> ] (226 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1/4	[hp]
2 Displacement	5.56	[cm <sup>3</sup> ] (0.339 cu.in)
2.1 Bore [mm]	22.500	
2.2 Stroke [mm]	14.000	
3 Lubricant charge	230	[ml] (7.78 fl.oz)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO7	
4 Weight (with oil charge)	9.9	[kg] (21.83 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	115-127 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	PTC	
2.1 Starting device	8EA14C3/8EA21C3/QPS2-A4R7MD3/QPS2-A4R7MD3 094	
3 Start capacitor	-	[µF(VAC minimum)]
4 Run capacitor	12(180)/15(200)/20(200)	[µF(VAC minimum)]
5 Motor protection	BT127-120	
6 Start winding resistance	6.94	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	4.88	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	11.30	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	1.70	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	2.07	[A] - Measured according to UL 984
11 Approval boards certification	CE - UKCA - UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @115V60Hz			ASHRAELBP32 Static		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
695	175	204	116	1.04	3.95	6.01	1.51	1.76

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 45°C (+113°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	335	85	98	75	0.67	1.90	4.49	1.13	1.32
-30 (-22)	497	125	146	92	0.82	2.82	5.38	1.36	1.58
-25 (-13)	700	176	205	110	0.98	3.97	6.32	1.59	1.85
-20 (- 4)	938	236	275	129	1.15	5.34	7.31	1.84	2.14
-15 (+ 5)	1207	304	354	146	1.31	6.89	8.34	2.10	2.44
-10 (+14)	1501	378	440	161	1.45	8.60	9.42	2.37	2.76

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 55°C (+131°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	286	72	84	66	0.61	1.62	4.34	1.09	1.27
-30 (-22)	426	107	125	86	0.78	2.42	4.99	1.26	1.46
-25 (-13)	616	155	180	108	0.97	3.50	5.70	1.44	1.67
-20 (- 4)	848	214	249	131	1.18	4.83	6.46	1.63	1.89
-15 (+ 5)	1119	282	328	154	1.39	6.39	7.26	1.83	2.13
-10 (+14)	1422	358	417	176	1.59	8.15	8.10	2.04	2.37

TEST CONDITIONS: @115V60Hz			ASHRAE32 Static		(Condensing temperature 65°C (+149°F))				
Evaporating temperature	Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C (°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-35 (-31)	224	56	66	59	0.55	1.27	3.77	0.95	1.10
-30 (-22)	340	86	100	80	0.72	1.93	4.33	1.09	1.27
-25 (-13)	512	129	150	104	0.93	2.91	4.95	1.25	1.45
-20 (- 4)	735	185	215	130	1.17	4.18	5.61	1.41	1.64
-15 (+ 5)	1004	253	294	158	1.43	5.73	6.31	1.59	1.85
-10 (+14)	1313	331	385	185	1.69	7.52	7.06	1.78	2.07

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal EG/F/AMEM version 2		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.1.1 Material	Copper		
3.1.2 Shape	Straight		
3.2 DISCHARGE	4.94 +0.08/-0.08	[mm]	(0.194" +0.003"/-0.003")
3.2.1 Material	Copper		
3.2.2 Shape	Straight		
3.3 PROCESS	6.5 +0.12/-0.08	[mm]	(0.256" +0.005"/-0.003")
3.3.1 Material	Copper		
3.3.2 Shape	Straight		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		