

COMPRESSOR DEFINITION

Designation	NT 2168GKV
Nominal Voltage/Frequency	208-230 V 60 Hz
Engineering Number	922ID04

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	208-230 / 60	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSIR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.50	[cm ³] (0.885 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	15.870	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	16.7	[kg] (36.82 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	208-230 V 60 Hz 1~ (Single phase)	
2 Starting device type	Current Relay	
2.1 Starting device	MTRPH0051-08	
3 Start capacitor	72-88(330)	[µF(VAC minimum)]
4 Run capacitor	-	[µF(VAC minimum)]
5 Motor protection	T0590/G9	
6 Start winding resistance	6.49	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.69	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (60 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (60 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (60 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	UL	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @208V60Hz			ASHRAELBP32 Fan		Evaporating temperature (Condensing temperature		-23.3°C (-9.94°F) 54.4°C (129.92°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
2694	679	789	619		18.26	4.35	1.10	1.27

E - PERFORMANCE - CURVES

TEST CONDITIONS: @208V60Hz			ASHRAE32 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1201	303	352	332	3.04	8.07	3.61	0.91	1.06
-35	(-31)	1688	425	494	410	3.27	11.38	4.13	1.04	1.21
-30	(-22)	2295	578	672	483	3.51	15.52	4.76	1.20	1.39
-25	(-13)	3022	762	886	552	3.76	20.53	5.47	1.38	1.60
-20	(- 4)	3871	975	1134	618	4.02	26.44	6.27	1.58	1.84
-15	(+ 5)	4840	1220	1418	678	4.28	33.26	7.13	1.80	2.09
-10	(+14)	5931	1495	1738	735	4.55	41.03	8.07	2.03	2.36

TEST CONDITIONS: @208V60Hz			ASHRAE32 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	1034	261	303	332	3.05	6.94	3.11	0.78	0.91
-35	(-31)	1491	376	437	411	3.29	10.03	3.63	0.91	1.06
-30	(-22)	2059	519	603	491	3.55	13.90	4.19	1.06	1.23
-25	(-13)	2738	690	802	572	3.85	18.56	4.78	1.20	1.40
-20	(- 4)	3529	889	1034	654	4.18	24.05	5.39	1.36	1.58
-15	(+ 5)	4431	1117	1298	738	4.53	30.38	6.01	1.51	1.76
-10	(+14)	5446	1372	1596	822	4.92	37.60	6.64	1.67	1.95

TEST CONDITIONS: @208V60Hz			ASHRAE32 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-40	(-40)	817	206	239	333	3.06	5.47	2.47	0.62	0.72
-35	(-31)	1262	318	370	411	3.29	8.48	3.07	0.77	0.90
-30	(-22)	1809	456	530	496	3.57	12.19	3.64	0.92	1.07
-25	(-13)	2458	619	720	587	3.91	16.63	4.19	1.06	1.23
-20	(- 4)	3210	809	940	684	4.31	21.83	4.70	1.18	1.38
-15	(+ 5)	4063	1024	1191	788	4.75	27.81	5.17	1.30	1.51
-10	(+14)	5020	1265	1471	898	5.24	34.59	5.58	1.41	1.63

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		