

COMPRESSOR DEFINITION

Designation	NT 6220GKV
Nominal Voltage/Frequency	200-240 V 50 Hz / 230 V 60 Hz
Engineering Number	922JN09

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	200-240 / 50	[V / Hz]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	3/4	[hp]
2 Displacement	14.50	[cm ³] (0.885 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	15.870	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17	[kg] (37.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	200-240 V 50 Hz / 230 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA4AL3C-649	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	17.5(440)	[µF(VAC minimum)]
5 Motor protection	T0590/G9	
6 Start winding resistance	12.16	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.86	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ	

D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @200V50Hz			EN12900MBP Fan		Evaporating temperature (Condensing temperature		-10°C (14°F) 45°C (113°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
3702	933	1085	625	3.18	32.59	5.92	1.49	1.73

E - PERFORMANCE - CURVES

TEST CONDITIONS: @200V50Hz		EN12900 Fan			(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2894	729	848	500	2.67	21.95	5.78	1.46	1.69
-15	(+ 5)	3705	934	1086	550	2.86	28.40	6.73	1.70	1.97
-10	(+14)	4660	1174	1366	598	3.03	36.02	7.80	1.96	2.28
-5	(+23)	5757	1451	1687	644	3.18	44.94	8.95	2.25	2.62
0	(+32)	6992	1762	2049	688	3.31	55.27	10.17	2.56	2.98
+5	(+41)	8363	2107	2451	731	3.42	67.12	11.44	2.88	3.35
+10	(+50)	9867	2487	2891	774	3.51	80.63	12.74	3.21	3.73

TEST CONDITIONS: @200V50Hz		EN12900 Fan			(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2319	584	679	518	2.68	20.05	4.49	1.13	1.32
-15	(+ 5)	2966	748	869	573	2.93	25.87	5.18	1.30	1.52
-10	(+14)	3740	943	1096	628	3.18	32.90	5.95	1.50	1.74
-5	(+23)	4637	1168	1359	682	3.41	41.26	6.79	1.71	1.99
0	(+32)	5654	1425	1657	736	3.65	51.07	7.67	1.93	2.25
+5	(+41)	6788	1711	1989	791	3.87	62.43	8.58	2.16	2.51
+10	(+50)	8038	2026	2355	848	4.10	75.48	9.49	2.39	2.78

TEST CONDITIONS: @200V50Hz		EN12900 Fan			(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	1830	461	536	536	2.72	18.59	3.41	0.86	1.00
-15	(+ 5)	2328	587	682	598	3.03	23.90	3.90	0.98	1.14
-10	(+14)	2933	739	859	661	3.35	30.46	4.44	1.12	1.30
-5	(+23)	3642	918	1067	725	3.68	38.37	5.03	1.27	1.47
0	(+32)	4454	1122	1305	791	4.01	47.76	5.64	1.42	1.65
+5	(+41)	5365	1352	1572	860	4.36	58.74	6.24	1.57	1.83
+10	(+50)	6373	1606	1867	932	4.72	71.43	6.83	1.72	2.00

F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal
2 Tray holder	No
3 Connectors	
3.1 SUCTION	12.7 +0.25/-0.25 [mm] (0.500" +0.010"/-0.010")
3.1.1 Material	Steel
3.1.2 Shape	ROTOLOCK(Ex. thr. 1"-14UNS-2A)
3.2 DISCHARGE	6.42 +0.08/+0.00 [mm] (0.253" +0.003"/+0.000")
3.2.1 Material	Copper
3.2.2 Shape	Vertical
3.3 PROCESS	6.42 +0.08/+0.00 [mm] (0.253" +0.003"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Vertical
3.4 Oil cooler (Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs