

### COMPRESSOR DEFINITION

Designation	NT 6222GKV
Nominal Voltage/Frequency	200-240 V 50 Hz / 230 V 60 Hz
Engineering Number	922KN04

### A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	200-240 / 50	[ V / Hz ]	
4 Application type	Medium Back Pressure (Commercial Compressors)		
4.1 Evaporating temperature range	-20°C to 10°C	(-4°F to 50°F)	
5 Motor type	CSCR		
6 Starting torque	HST - High starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing temperature			
9.1 Operating	25.2	[kgf/cm <sup>2</sup> ] (358 psig)	/ °C - °F
9.2 Peak	28.3	[kgf/cm <sup>2</sup> ] (402 psig)	/ °C - °F
10 Maximum winding temperature	130	[ °C ]	

### B - MECHANICAL DATA

1 Commercial designation	1	[hp]
2 Displacement	17.39	[cm <sup>3</sup> ] (1.061 cu.in)
2.1 Bore [mm]	34.120	
2.2 Stroke [mm]	19.030	
3 Lubricant charge	450	[ml] (15.22 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	17	[kg] (37.48 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm <sup>2</sup> ] (2.84 to 4.27 psig)

### C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	200-240 V 50 Hz / 230 V 60 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA3N3C-122	
3 Start capacitor	130-156(250)	[µF(VAC minimum)]
4 Run capacitor	17.5(440)	[µF(VAC minimum)]
5 Motor protection	T0748/G9	
6 Start winding resistance	10.10	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.75	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification	IMQ - IRAM - UL	

### D - PERFORMANCE - CHECK POINT DATA

TEST CONDITIONS: @200V50Hz			EN12900MBP Fan		Evaporating temperature (Condensing temperature		-10°C (14°F) 45°C (113°F)	
Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
4462	1124	1307	769	4.08	39.27	5.80	1.46	1.70

### E - PERFORMANCE - CURVES

TEST CONDITIONS: @200V50Hz			EN12900 Fan		(Condensing temperature 35°C (+95°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	3371	849	988	600	3.25	25.59	5.61	1.41	1.64
-15	(+ 5)	4308	1086	1262	657	3.52	33.00	6.56	1.65	1.92
-10	(+14)	5440	1371	1594	717	3.80	42.03	7.58	1.91	2.22
-5	(+23)	6746	1700	1977	778	4.09	52.66	8.67	2.18	2.54
0	(+32)	8204	2067	2404	838	4.38	64.87	9.80	2.47	2.87
+5	(+41)	9794	2468	2870	894	4.68	78.63	10.97	2.76	3.21
+10	(+50)	11495	2897	3368	945	4.99	93.91	12.15	3.06	3.56

TEST CONDITIONS: @200V50Hz			EN12900 Fan		(Condensing temperature 45°C (+113°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2763	696	810	643	3.47	23.90	4.31	1.09	1.26
-15	(+ 5)	3522	888	1032	703	3.77	30.71	5.02	1.26	1.47
-10	(+14)	4461	1124	1307	769	4.08	39.24	5.79	1.46	1.70
-5	(+23)	5560	1401	1629	838	4.40	49.48	6.61	1.67	1.94
0	(+32)	6797	1713	1992	909	4.74	61.39	7.47	1.88	2.19
+5	(+41)	8151	2054	2388	978	5.09	74.96	8.34	2.10	2.44
+10	(+50)	9602	2420	2814	1043	5.45	90.17	9.22	2.32	2.70

TEST CONDITIONS: @200V50Hz			EN12900 Fan		(Condensing temperature 55°C (+131°F))					
Evaporating temperature		Cooling capacity +/- 5%			Power consumption +/- 5%	Current consumption +/- 5%	Gas flow rate +/- 5%	EFFICIENCY RATE +/- 7%		
°C	(°F)	[Btu/h]	[kcal/h]	[W]	[W]	[A]	[kg/h]	[Btu/Wh]	[kcal/Wh]	[W/W]
-20	(- 4)	2278	574	668	694	3.70	23.12	3.26	0.82	0.96
-15	(+ 5)	2831	714	830	758	4.04	29.09	3.75	0.94	1.10
-10	(+14)	3550	895	1040	831	4.40	36.90	4.28	1.08	1.26
-5	(+23)	4414	1112	1294	909	4.78	46.51	4.86	1.22	1.42
0	(+32)	5403	1361	1583	990	5.18	57.91	5.45	1.37	1.60
+5	(+41)	6494	1637	1903	1073	5.60	71.07	6.05	1.53	1.77
+10	(+50)	7668	1932	2247	1154	6.04	85.97	6.64	1.67	1.95

### F - EXTERNAL CHARACTERISTICS

1 Base plate	Universal		
2 Tray holder	No		
3 Connectors			
3.1 SUCTION	9.6 +0.07/+0.00	[mm]	(0.378" +0.003"/+0.000")
3.1.1 Material	Copper		
3.1.2 Shape	Vertical		
3.2 DISCHARGE	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.2.1 Material	Copper		
3.2.2 Shape	Vertical		
3.3 PROCESS	6.42 +0.08/+0.00	[mm]	(0.253" +0.003"/+0.000")
3.3.1 Material	Copper		
3.3.2 Shape	Vertical		
3.4 Oil cooler (Copper)	No	[mm]	
3.5 Connector sealing	Rubber Plugs		