

COMPRESSOR DEFINITION

Designation	NJ 2212GK
Nominal Voltage/Frequency	220-240 V 50 Hz
Engineering Number	943DA19

A - APPLICATION / LIMIT WORKING CONDITIONS

1 Type	Hermetic reciprocating compressor		
2 Refrigerant	R-404A		
3 Nominal voltage and frequency	220-240 / 50	[V / Hz]	
4 Application type	Low Back Pressure R404A		
4.1 Evaporating temperature range	-40°C to -10°C	(-40°F to 14°F)	
5 Motor type	CSCR		
6 Starting torque	HST - Hight starting torque		
7 Expansion device	Capillary tube or Expansion valve		
8 Compressor cooling	Operating voltage range		
		50 Hz	60 Hz
8.1 LBP (32°C Ambient temperature)	-	-	-
8.2 LBP (43°C Ambient temperature)	-	-	-
8.3 HBP (32°C Ambient temperature)	-	-	-
8.4 HBP (43°C Ambient temperature)	-	-	-
9 Maximum condensing pressures/temperature			
9.1 Operating (gauge)	25.7	[kgf/cm ²] (365 psig)	/ °C - °F
9.2 Peak (gauge)	28.7	[kgf/cm ²] (408 psig)	/ °C - °F
10 Maximum winding temperature	130	[°C]	

B - MECHANICAL DATA

1 Commercial designation	1 1/2	[hp]
2 Displacement	34.38	[cm ³] (2.098 cu.in)
2.1 Bore [mm]	42.850	
2.2 Stroke [mm]	23.850	
3 Lubricant charge	750	[ml] (25.36 fl.oz.)
3.1 Lubricants approved		
3.2 Lubricants type/viscosity	ESTER / ISO22	
4 Weight (with oil charge)	21.5	[kg] (47.40 lb.)
5 Nitrogen charge	0.2 to 0.3	[kgf/cm ²] (2.84 to 4.27 psig)

C - ELETRICAL DATA

1 Nominal Voltage/Frequency/Number of Phases	220-240 V 50 Hz 1 ~ (Single phase)	
2 Starting device type	Voltage Relay	
2.1 Starting device	RVA2L3C-112	
3 Start capacitor	88-108(330)	[µF(VAC minimum)]
4 Run capacitor	20(440)	[µF(VAC minimum)]
5 Motor protection	15HM2445-168	
6 Start winding resistance	4.84	[Ω at 25°C (77°F)] +/- 8%
7 Run winding resistance	1.70	[Ω at 25°C (77°F)] +/- 8%
8 LRA - Locked rotor amperage (50 Hz)	-	[A] - Measured according to UL 984
9 FLA - Full load amperage L/MBP (50 Hz)	-	[A] - Measured according to UL 984
10 FLA - Full Load Amperage HBP (50 Hz)	-	[A] - Measured according to UL 984
11 Approval boards certification		

D - PERFORMANCE - CHECK POINT DATA

E - PERFORMANCE - CURVES

F - EXTERNAL CHARACTERISTICS

1 Base plate	American Standard
2 Tray holder	No
3 Connectors	
3.1 SUCTION	12.7 +0.25/-0.25 [mm] (0.500" +0.010"/-0.010")
3.1.1 Material	Steel
3.1.2 Shape	ROTOLOCK(Ex. thr. 1"-14UNS-2A)
3.2 DISCHARGE	8 +0.07/+0.00 [mm] (0.315" +0.003"/+0.000")
3.2.1 Material	Copper
3.2.2 Shape	Slanted J
3.3 PROCESS	6.42 +0.08/+0.00 [mm] (0.253" +0.003"/+0.000")
3.3.1 Material	Copper
3.3.2 Shape	Vertical
3.4 Oil cooler (Copper)	No [mm]
3.5 Connector sealing	Rubber Plugs